

```

%_mprintto;
options notes nosource;
proc datasets lib=work nolist memtype=data kill; quit;
%put NOTE:
=====;
%put NOTE: Covance Study Number : 000000106324;
%put NOTE: Client Protocol ID   : ZRHR-REXC-03-EU;
%put NOTE: Program Name        : f_1na24.sas;
%put NOTE: Purpose              : Figure of 1na excreted over 24 hours;
%put NOTE: ;
%put NOTE: Input Data           : ADAM.ADBX;
%put NOTE: Output               : f_15_1_2_12(1na24);
%put NOTE: Macros Called        : _MPRINTTO;
%put NOTE: ;
%put NOTE: Programmed by        : cvn_jriley;
%put NOTE: Creation Date        : 2014-06-12;
%put NOTE: SAS Version          : 9.3;
%put NOTE: ;
%put NOTE: == Latest Run
=====;
%put NOTE: Run by                : &sysuserid;
%put NOTE: Date/Time             :
%sysfunc(putn(%sysfunc(date()),e8601da.))T%sysfunc(putn(%sysfunc(time()),
e86011z.));
%put NOTE: ;
%put NOTE: == Modification History
=====;
%put NOTE: Date      Initials   No. Reason;
%put NOTE: 15Sep2014   JMH       1) Added XLS file;
%put NOTE: 15Sep2014   JMH       2) Amended titles and footnotes;
%put NOTE: ;
%put NOTE:
=====;
options notes source source2 nofullstimer validvarname=upcase missing='
';
ods _all_ close;
ods listing;

*=====;
* START OF PROGRAM CODE                                     ;
*=====;

/* Standard - just change the number to match the listing you're working
on. Also change the letters in the*/
/* bracket, eg ccb = current cigarette brands. Make sure to do this at
the top of the code too. */
%let tflno=F_15_01_02_12(1na24);

/* Standard - leave this */
%let TFL_Part=%scan(&_SASPROGRAMFILE,-3,%str(/));

/* Standard - leave this */
data _null_;

```

```

    tmp="%TFL_Part";
    if tmp not in ("dev" "qc") then call symput("TFL_Part", "prod");
    call symput('TFLpath', compress("&_SASPROGRAMFILE", ""));
run;

/* Example of basic GTL syntax */
ods _all_ close;
%let temp=/cvn/projects/prj/development/000000106324/dev/macro/;

/* Ensure ODS listing, html etc is turned off to prevent */
/* temporary or junk image files being produced */
options notes source source2 nofullstimer validvarname=upcase
nonumber nodate orientation=portrait papersize=&p_pgsz missing=' ';
ods graphics on; /* As we are effectively using ODS graphics we need to
ensure that it is turned on */
ods graphics / height=12cm width=16cm noborder; /* Removes border around
the image */
ods path reset;
/* please include styles template */
%include "&temp.figtmp.sas";

ods rtf toc_data
file="/cvn/projects/prj/data/000000106324/TFL/&TFL_Part/&tflno..rtf"
style=t106324_g startpage=yes headery=1440 footery=1440 ;

ods exclude all;

data adbx1;
    set adam.adbx(where=(anl02fl='Y' and fasfl ='Y' and lbstat ne 'NOT
DONE' and paramcd in ('U1NA24U')));
run;

data adbx2;
    set adbx1;
    if ablfl='Y' then avisit='Baseline';
    if avisit ne 'Baseline' and avisitn lt 101 then delete;
    if avisit='Baseline' then avisit='Day 0';
run;

data gmean;
    set adbx2;
    statval=aval;
    if statval ne 0 then ln_statval=log(statval);
    else gflag=1;
run;

proc sort data=gmean; by param avalu trtan trta avisitn avisit; run;

proc means data=gmean(where=(gflag=1)) noprint;
    output out=gmeanla(keep=param avalu trtan trta avisitn avisit gflag)
mean=mean ;

```

```

    var ln_statval;
    by param avalu trtan trta avisitn avisit gflag;
run;

proc means data=gmean alpha=0.05 noprint;
    output out=gmeanlb mean=mean std=stdl lclm=lcll uclm=ucll;
    var ln_statval;
    by param avalu trtan trta avisitn avisit;
run;

data gmean2;
    merge gmeanla gmeanlb;
    by param avalu trtan trta avisitn avisit;
    attrib tpt format = best.;

if gflag ne 1 then do;
    gmean=exp(mean);
    lclm=exp(lcll);
    uclm=exp(ucll);
end;

    avisit1=left(strip(tranwrd(avisit,'Day ','')));
    tpt=input(avisit1,best.);

    keep param avalu trtan trta avisitn avisit gmean lclm uclm tpt;
run;

/*Use a proc summary to find the maximum value of the Y axis which needs
to be presented for the first plot*/
proc summary data=gmean2;
    by param;
    var uclm;
    output out =axis1 max=max1;
run;

data maxaxis1;
    set axis1;
    max2=(ceil(max1));

    /*Use mod 2 to ensure axis limit is an even number so the increment
can be 2*/
    if mod(max2,2)=0 then max=max2;
    else if mod(max2,2)=1 then max=max2+1;

    keep param max max2 max1;
run;

data adbx3;
    merge gmean2 maxaxis1;
    by param;

    if avisitn=99 then delete;
run;

```

```

/* 1) start JMH 15Sep2014 */
PROC SQL;
CREATE TABLE ADBX3_X AS
SELECT PARAM, TRTA, AVISIT, GMEAN, LCLM, UCLM
FROM ADBX3;
QUIT;

PROC EXPORT
DATA=ADBX3_X
DBMS=XLSX
OUTFILE="/cvn/projects/prj/data/000000106324/TFL/&TFL_Part./&tflno..xlsx"
REPLACE;
SHEET=Sheet1;
/* 1) end JMH 15Sep2014 */

proc format;
    value xaxis
        0='Baseline'
        1='1'
        2='2'
        3='3'
        4='4'
        5='5';

run;

title;
footnote;

data paging; /* paging is derived normally as with RTF type TFL */

    set adbx3 end=last;
    page = 1;
    if last then call symput("maxpage", compress(page));

run;

%macro graph();

%do i=1 %to &maxpage; /* paging can either be done through a do loop or
multiple macro calls */

    data plot;
        set paging;
        where page = &i;
        call symput("unit", strip(avalu));
        call symput("max1", max);
    run;

proc template;
    define statgraph splot /store = work.templat;
        begingraph /;

```

```

/*          entrytitle halign=left "Figure 15.1.2.12 Urinary 1-NA
Quantity Excreted over 24 hours (&unit) Geometric Mean and 95% CI - FAS"
/*;*/ /* 2) JMH 15Sep2014 */
/*          entrytitle halign=left " " /*;*/ /* 2) JMH 15Sep2014 */
          layout overlay / border=false
axisopts=(linearopts=(tickvaluesequence=(start=0 end=5 increment=1))
label="Study Day") yaxisopts=(linearopts=(tickvaluesequence=(start=0
end=175 increment=25) viewmin=0 viewmax=175) label="1-NA (&unit)")
cycleattrs=false;
          seriesplot x=tpt y=gmean / index=trtan primary=true
group=trta display=(markers) legendlabel="mean" name="series";
          /*referenceline y=0.5 / ;*/ /*This would be the BLOQ
value*/
          scatterplot x=tpt y=gmean / index=trtan group=trta
yerrorlower=lclm yerrorupper=uclm
          legendlabel="mean" name="scatter" ;
          discretelegend "series";
          endlayout;
          /* footnotes work using the same option as the entrytitle
statement */
/* 2) start JMH 15Sep2014 */
/*          entryfootnote halign=left " " ;*/
/*          entryfootnote halign=left
"Note: CC = Conventional cigarettes; SA = Smoking abstinence; THS =
Tobacco Heating System." ;*/
/*          entryfootnote halign=left
"Baseline is defined as the last assessment prior to 06:29 AM on Day 1." ;
*/
/*          entryfootnote halign=left "
";*/
/*          entryfootnote halign=left "Appendix 15.2.4.16";*/
/*          entryfootnote halign=left "Path: &TFLpath."
halign=right "(Page &i of &maxpage)"; */
/*          entryfootnote halign=left "Program Run: &sysdate
&sysuserid Program Status: &status";*/
/* 2) end JMH 15Sep2014 */
          endgraph;
        end;
      run;

ods select all;

/* 2) start JMH 15Sep2014 */
ODS ESCAPECHAR='^';
ODS RTF PREPAGE="^S={outputwidth=100% just=l font_size=12pt
font_weight=bold background=white foreground=black
font_face=arial}^R/RTF'\QL' Figure 15.1.2.12 Urinary 1-NA Quantity
Excreted over 24 hours (&unit) Geometric Mean and 95% CI - FAS";
/* 2) end JMH 15Sep2014 */

proc sgrender data=plot template=plot; /* applies the above
template to the specified data */
          format tpt xaxis.;
run;

```

```

/* 2) start JMH 15Sep2014 */
ODS RTF TEXT="^S={outputwidth=100% just=l font_size=9pt background=white
foreground=black font_face=arial}^R/RTF'\QL'";
ODS RTF TEXT="^S={outputwidth=100% just=l font_size=9pt background=white
foreground=black font_face=arial}^R/RTF'\QL' Note: CC = Conventional
cigarettes; SA = Smoking abstinence; THS = Tobacco Heating System.";
ODS RTF TEXT="^S={outputwidth=100% just=l font_size=9pt background=white
foreground=black font_face=arial}^R/RTF'\QL' Note: Baseline is the last
assessment prior to first product use in CC/THS 2.2 arms on Day 1 or last
assessment prior to 06:29 AM in SA arm on Day 1.";
ODS RTF TEXT="^S={outputwidth=100% just=l font_size=9pt background=white
foreground=black font_face=arial}^R/RTF'\QL'";
ODS RTF TEXT="^S={outputwidth=100% just=l font_size=9pt background=white
foreground=black font_face=arial}^R/RTF'\QL' Appendix 15.2.4.16";
ODS RTF TEXT="^S={outputwidth=100% just=l font_size=9pt background=white
foreground=black font_face=arial}^R/RTF'\QL' Path: &TFLpath.
(Page &i of &maxpage)";
ODS RTF TEXT="^S={outputwidth=100% just=l font_size=9pt background=white
foreground=black font_face=arial}^R/RTF'\QL' Program Run: &sysdate
&sysuserid Program Status: &status";

/* 2) end JMH 15Sep2014 */

%end;
%mend graph;
%graph;
proc printto ; run;
ods exclude all;
ods _all_ close;
ods graphics / reset;

```