

```

%_mprintto;
options notes nosource;
proc datasets lib=work nolist memtype=data kill; quit;
%put NOTE:
=====;
%put NOTE: Covance Study Number : 000000106324;
%put NOTE: Client Protocol ID   : ZRHR-REXC-03-EU;
%put NOTE: Program Name        : f_bap24.sas;
%put NOTE: Purpose             : Figure of BAP excreted over 24 hrs FAS;
%put NOTE: ;
%put NOTE: Input Data           : ADAM.ADBX;
%put NOTE: Output               : F_15_1_2_22(bap);
%put NOTE: Macros Called        : _MPRINTTO;
%put NOTE: ;
%put NOTE: Programmed by        : cvn_kbooth;
%put NOTE: Creation Date        : 2015-10-21;
%put NOTE: SAS Version          : 9.3;
%put NOTE: ;
%put NOTE: == Latest Run
=====;
%put NOTE: Run by                : &sysuserid;
%put NOTE: Date/Time             :
%sysfunc(putn(%sysfunc(date()),e8601da.))T%sysfunc(putn(%sysfunc(time()),
e86011z.));
%put NOTE: ;
%put NOTE: == Modification History
=====;
%put NOTE: Date      Initials   No. Reason;
%put NOTE: ;
%put NOTE:
=====;
options notes source source2 nofullstimer validvarname=upcase missing='
';
ods _all_ close;
ods listing;

*=====;
* START OF PROGRAM CODE
*=====;

/* Standard - just change the number to match the listing you're working
on. Also change the letters in the*/
/* bracket, eg ccb = current cigarette brands. Make sure to do this at
the top of the code too. */
%let tflno=F_15_01_02_22(bap);

/* Standard - leave this */
%let TFL_Part=%scan(&_SASPROGRAMFILE,-3,%str(/));

/* Standard - leave this */
data _null_;
  tmp="&TFL_Part";
  if tmp not in ("dev" "qc") then call symput("TFL_Part", "prod");

```

```

        call symput('TFLpath', compress("&_SASPROGRAMFILE",""));
run;

/* Example of basic GTL syntax */
ods _all_ close;
%let temp=/cvn/projects/prj/development/000000106324/dev/macro/;

/* Ensure ODS listing, html etc is turned off to prevent */
/* temporary or junk image files being produced */
options notes source source2 nofullstimer validvarname=upcase
nonumber nodate orientation=portrait papersize=&p_pgsz missing=' ';
ods graphics on; /* As we are effectively using ODS graphics we need to
ensure that it is turned on */
ods graphics / height=12cm width=16cm noborder; /* Removes border around
the image */
ods path reset;
/* please include styles template */
%include "&temp.figtmp.sas";

ods rtf toc_data
file="/cvn/projects/prj/data/000000106324/TFL/&TFL_Part/&tflno..rtf"
style=t106324_g startpage=yes headery=1440 footery=1440 ;

ods exclude all;

data adbx1;
    set adam.adbx(where=(anl02fl='Y' and fasfl ='Y' and lbstat ne 'NOT
DONE' and paramcd in ('UBAP24U')));
run;

data adbx2;
    set adbx1;
    if ablfl='Y' then avisit='Baseline';
    if avisit ne 'Baseline' and avisitn lt 101 then delete;
    if avisit='Baseline' then avisit='Day 0';
run;

data gmean;
    set adbx2;
    statval=aval;
    if statval ne 0 then ln_statval=log(statval);
    else gflag=1;
run;

proc sort data=gmean; by param avalu trtan trta avisitn avisit; run;

proc means data=gmean(where=(gflag=1)) noprint;
    output out=gmeanla(keep=param avalu trtan trta avisitn avisit gflag)
mean=mean ;
    var ln_statval;
    by param avalu trtan trta avisitn avisit gflag;

```

```

run;

proc means data=gmean alpha=0.05 noprint;
  output out=gmean1b mean=mean std=std1 lclm=lci1 uclm=uci1;
  var ln_statval;
  by param avalu trtan trta avisitn avisit;
run;

data gmean2;
  merge gmean1a gmean1b;
  by param avalu trtan trta avisitn avisit;
  attrib tpt format = best.;

if gflag ne 1 then do;
  gmean=exp(mean);
  lclm=exp(lci1);
  uclm=exp(uci1);
end;

  avisit1=left(strip(tranwrd(avisit,'Day ','')));
  tpt=input(avisit1,best.);

  keep param avalu trtan trta avisitn avisit gmean lclm uclm tpt;
run;

/*Use a proc summary to find the maximum value of the Y axis which needs
to be presented for the first plot*/
proc summary data=gmean2;
  by param;
  var uclm;
  output out =axis1max max=max1;
run;

proc summary data=gmean2;
  by param;
  var lclm;
  output out =axis1min min=min1;
run;

data maxaxis1;
  merge axis1max axis1min;
  by param;

  max2=(ceil(max1));
  min2=(floor(min1));

  /*Use mod 2 to ensure axis limit is an even number so the increment
can be 2*/
  if mod(max2,2)=0 then max=max2;
  else if mod(max2,2)=1 then max=max2+1;

  if mod(min2,2)=0 then min=min2;
  else if mod(min2,2)=1 then min=min2-1;

```

```

        keep param max: min;;
run;

data adbx3;
    merge gmean2 maxaxis1;
    by param;

    if avisitn=99 then delete;

run;

proc sql;
create table adbx3_x as
select param, trta, avisit, gmean, lclm, uclm
from adbx3;
quit;

proc export
data=adbx3_x
dbms=xlsx
outfile="/cvn/projects/prj/data/000000106324/TFL/&TFL_Part./&tflno..xlsx"
replace;
sheet=sheet1;

proc format;
    value xaxis
        0='Baseline'
        1='1'
        2='2'
        3='3'
        4='4'
        5='5';

run;
title;
footnote;

data paging; /* paging is derived normally as with RTF type TFL */

    set adbx3 end=last;
    page = 1;
    if last then call symput("maxpage", compress(page));

run;

%macro graph();

%do i=1 %to &maxpage; /* paging can either be done through a do loop or
multiple macro calls */

    data plot;

```

```

        set paging;
        where page = &i;
        call symput("unit",strip(avalu));
        call symput("max1",max);
run;

proc template;
    define statgraph splot /store = work.templat;
        begingraph /;
            layout overlay / border=false
axisopts=(linearopts=(tickvaluesequence=(start=0 end=5 increment=1))
label="Study Day") yaxisopts=(linearopts=(tickvaluesequence=(start=0
end=500 increment=50) viewmin=0 viewmax=500) label="B[a]P (&unit)")
cycleattrs=false;
                seriesplot x=tpt y=gmean / index=trtan primary=true
group=trta display=(markers) legendlabel="mean" name="series";
                scatterplot x=tpt y=gmean / index=trtan group=trta
yerrorlower=lclm yerrorupper=uclm
                legendlabel="mean" name="scatter" ;
                discretelegend "series";
            endlayout;
        endgraph;
    end;
run;

ods select all;

ods escapechar='^';
ods rtf prepage="^S={outputwidth=100% just=l font_size=12pt
font_weight=bold background=white foreground=black
font_face=arial}^R/RTF'\QL' Figure 15.1.2.22 Urinary B[a]P Quantity
Excreted over 24 hours (&unit) Geometric Mean and 95% CI - FAS";

        proc sgrender data=plot template=splot; /* applies the above
template to the specified data */
            format tpt xaxis.;
run;

ods rtf text="^S={outputwidth=100% just=l font_size=9pt background=white
foreground=black font_face=arial}^R/RTF'\QL'";
ods rtf text="^S={outputwidth=100% just=l font_size=9pt background=white
foreground=black font_face=arial}^R/RTF'\QL' Note: CC = Conventional
cigarettes; SA = Smoking abstinence; THS = Tobacco Heating System.";
ods rtf text="^S={outputwidth=100% just=l font_size=9pt background=white
foreground=black font_face=arial}^R/RTF'\QL' Note: Baseline is the last
assessment prior to first product use in CC/THS 2.2 arms on Day 1 or last
assessment prior to 06:29 AM in SA arm on Day 1.";
ods rtf text="^S={outputwidth=100% just=l font_size=9pt background=white
foreground=black font_face=arial}^R/RTF'\QL'";
ods rtf text="^S={outputwidth=100% just=l font_size=9pt background=white
foreground=black font_face=arial}^R/RTF'\QL' Appendix 15.2.4.26";
ods rtf text="^S={outputwidth=100% just=l font_size=9pt background=white
foreground=black font_face=arial}^R/RTF'\QL' Path: &TFLpath.
(Page &i of &maxpage)";

```

```
ods rtf text="^S={outputwidth=100% just=l font_size=9pt background=white  
foreground=black font_face=arial}^R/RTF'\QL' Program Run: &sysdate  
&sysuserid   Program Status: &status";
```

```
%end;
```

```
%mend graph;
```

```
%graph;
```

```
proc printto ; run;
```

```
ods _all_ close;
```

```
ods graphics / reset;
```