

```

%_mprintto;
options notes nosource;
proc datasets lib=work nolist memtype=data kill; quit;
%put NOTE:
=====;
%put NOTE: Covance Study Number : 000000106324;
%put NOTE: Client Protocol ID   : ZRHR-REXC-03-EU;
%put NOTE: Program Name        : t_bma.sas;
%put NOTE: Purpose              : table decriptive stats of S_BMA ;
%put NOTE: ;
%put NOTE: Input Data           : ADAM.ADBX ADAM.ADSL;
%put NOTE: Output               : t_15_2_4_30(sbma);
%put NOTE: Macros Called        : _MPRINTTO;
%put NOTE: ;
%put NOTE: Programmed by        : cvn_jhardman;
%put NOTE: Creation Date        : 2014-07-24;
%put NOTE: SAS Version          : 9.3;
%put NOTE: ;
%put NOTE: == Latest Run
=====;
%put NOTE: Run by                : &sysuserid;
%put NOTE: Date/Time             :
%sysfunc(putn(%sysfunc(date()),e8601da.))T%sysfunc(putn(%sysfunc(time()),
e86011z.));
%put NOTE: ;
%put NOTE: == Modification History
=====;
%put NOTE: Date      Initials   No. Reason;
%put NOTE: 03Sep2014  JR         1) Added nmiss to proc means to check
for missing subjects;
%put NOTE: 18Sep2014  JR         2) Updated baseline footnote;
%put NOTE: 18Sep2014  JMH        3) Amended stats;
%put NOTE: 25Sep2014  JMH        4) Amended BLQ calculations and
presentation;
%put NOTE: 03OCT2014  JH         5) Amended BLQ count when 0 for chg
column;
%put NOTE: ;
%put NOTE:
=====;
options notes source source2 nofullstimer validvarname=upcase missing='
';
ods _all_ close;
ods listing;

*=====;
* START OF PROGRAM CODE
*=====;

%let tflno=T_15_02_04_30(sbma);

%let TFL_Part=%scan(&_SASPROGRAMFILE,-3,%str(/));

data _null_;
    tmp("&TFL_Part");

```

```

        if tmp not in ("dev" "qc") then call symput("TFL_Part", "prod");
        call symput('TFLpath', compress("&_SASPROGRAMFILE", ""));
run;

*****;
* read in data ;
*****;

/*Use ADSL to get N values for column headers*/
data adsl;
    set adam.adsl(where=(fasfl='Y'));
run;

proc sort data=adsl nodupkey out=adsl1;
    by trt01an trt01a subjid;
run;

proc freq data=adsl1(where=(not missing(trt01an))) noprint;
    table trt01an*trt01a/ out =tot(drop=percent rename=(count=total));
run;

data tot2;
    set tot;
    call symput('trt' || compress(put(trt01an,best.)),
compress(total));
run;

/*Bring in appropriate data from ADBX*/
data adbx1;
    set adam.adbx(where=(anl02fl='Y' and fasfl='Y' and paramcd in
('USBMA24U' 'USBMACRE')));
    if ablfl='Y' then do; avisit='Baseline'; avisitn=100; end;
    if avisit ne 'Baseline' and avisitn lt 101 then delete;
run;

data adbx;
    set adbx1;
run;

data adbx_orig;
    set adbx;
    statval=aval;
    type='abs';
    output;
    statval=pchg;
    type='pchg';
    output;
run;

proc sort data=adbx_orig;
    by type paramn param trtan trta avisitn avisit atptn atpt;
run;

```

```

proc means data=adbx_orig noprint;
  var statval;
  by type paramn param trtan trta avisitn avisit atptn atpt;
  output out=results02 n=n1 NMISS=MISS mean=mean1 std=std1
median=median1 min=min1 max=max1 q1=q1 q3=q3 lclm=lci1 uclm=uci1; /* 1)
JR 03Sep2014 */
run;

data results03;
  set results02;
  attrib meansd length=$30.
           minmax length=$30.
           n      length=$30.
           median length=$30.
           quart  aci length=$30.;

  n = left(compress(put(n1,8.)));
  if not missing(median1) then median =
left(compress(put(round(median1,0.01),10.2)));
  if not missing(mean1) and not missing(std1) then meansd =
left(compress(put(round(mean1,0.01),10.2))) || ' (' ||
left(compress(put(0.001*ceil(std1/0.001),10.3))) || ')';
  if not missing(min1) and not missing(max1) then minmax =
left(compress(put(round(min1,0.1),10.1))) || ', ' ||
left(compress(put(round(max1,0.1),10.1)));
  if not missing(lci1) and not missing(uci1) then aci =
strip(put(0.01*floor(lci1/0.01),10.2)) || ', ' ||
strip(put(0.01*ceil(uci1/0.01),10.2));
/*      if not missing(q1) and not missing(q3) then quart =
strip(put(0.01*floor(q1/0.01),10.2)) || ', ' ||
strip(put(0.01*ceil(q3/0.01),10.2));          */
  IF NOT MISSING(Q1) AND NOT MISSING(Q3) THEN QUART =
STRIP(PUT(0.01*FLOOR(Q1*100),10.2)) || ', ' ||
STRIP(PUT(0.01*CEIL(Q3*100),10.2));          /* 3) JMH 18Sep2014 */

  drop /*n1*/ mean1 std1 median1 min1 max1 q1 q3 uci1 lci1 ; /* 4) JMH
25Sep2014 */
run;

```

```

/*Obtain subjects with values BLOQ*/
data adbx_blq;
  set adbx;
  where bloqfl='Y';
  statval=aval;
  type='abs';
  output;
  statsval=pchg;
  type='pch';
  output;
run;

```

```

proc freq data=adbx_blq noprint;
    table type*paramn*param*trtan*trta*avisitn*avisit*atptn*atpt/ out
    =blq(drop=percent);
run;

%macro outrtf(blankn=, halfblnk=);

%if &halfblnk=N %then %let halfblnk=;
%else %if &halfblnk=Y %then %let halfblnk=\~;

%let dsid=%sysfunc(open(blq));
%let nsum=%sysfunc(attrn(&dsid.,nobs));
%let rc=%sysfunc(close(&dsid.));

%put "Check " &nsum.;

%if &nsum. lt 1 %then %do;
    proc sort data=adbx_orig nodupkey out=tpts(keep=type paramn
    param avisitn avisit atptn atpt trtan trta);
        by paramn param trtan trta type avisitn avisit atptn
    atpt;
    run;

    data blq1;
        set tpts;
        attrib blq length=$50.;
        blq='0';
    run;
%end;

%else %do;
    proc sort data=adbx_orig nodupkey out=tpts(keep=type paramn param
    avisitn avisit atptn atpt trtan trta);
        by trtan trta type paramn param avisitn avisit atptn
    atpt;
    run;

/* 4) start JMH 25Sep2014 */
    DATA BLQTOTS;
        SET RESULTS03(RENAME=(N1=TOTAL));
        KEEP TYPE PARAM: TR: AVISIT: ATPT: TOTAL;
    RUN;

    PROC SORT DATA=BLQTOTS; by TYPE trtan trta PARAMN PARAM
    AVISITN AVISIT; RUN;
    PROC SORT DATA=TPTS; by TYPE trtan trta PARAMN PARAM AVISITN
    AVISIT; RUN;

    data tot_blq;
        merge tpts /*tot(rename=(trt01an=trtan
    trt01a=trta))*/BLQTOTS;
        by TYPE trtan trta PARAMN PARAM AVISITN AVISIT;
    run;

```

```

/* 4) end JMH 25Sep2014 */

proc sort data=tot_blq;
  by type paramn param trtan trta avisitn avisit atptn
atpt;
run;

data blq1;
  attrib blq length=$50.;
  merge blq(in=a) tot_blq;
  by type paramn param trtan trta avisitn avisit atptn
atpt;

  if not a then do;
    count=0;
  end;
  IF TOTAL NE 0 THEN percent=count/total*100; /* 4) JMH
25Sep2014 */
  ELSE PERCENT=0; /* 4) JMH 25Sep2014 */

  if count=0 then blq='0';
  else if percent=100 then blq= put(count,3.)||' (100%)';
  else blq=put(count,3.)||'
('||left(strip(put(round(percent,0.1),5.1)))||'%)';

  if type='pch' then blq='';
run;
%end;

/*Obtain the geometric mean*/

data gmean;
  set adbx_orig(where=(type='abs'));
  statvall=statval;
  ln_statvall=log(statvall);
run;

proc means data=gmean noprint;
  output out=gmean1 mean=mean std=std1 lclm=lci1 uclm=uci1;
  var ln_statvall;
  by paramn param trtan trta type avisitn avisit atptn atpt;
run;

data gmean2;
  set gmean1;
  gmean1=exp(mean);
  gmean=left(compress(put(round(gmean1,0.01),10.2)));
  gcv=compress(put(0.01*ceil((sqrt(exp(std1*std1)-1)*100)/0.01),10.2));
  glci=exp(lci1);
  guci=exp(uci1);
  keep type paramn param trtan trta avisitn avisit atptn atpt gmean gcv
  glci guci std1;
run;

```

```

/*Combine the Gmean and BLQ with other stats*/
proc sort data=results03;
  by paramn param trtan trta type avisitn avisit atptn atpt;
run;

proc sort data=blq1;
  by paramn param trtan trta type avisitn avisit atptn atpt;
run;

data results04;
  merge results03 gmean2 blq1;
  attrib gmeancv length=$30.;
  by paramn param trtan trta type avisitn avisit atptn atpt;
  if not missing(gcv) then gmeancv=left(trim(gmean)) || ' (' ||
left(trim(gcv))||'%)';
  else gmeancv=left(trim(gmean));
  if not missing(glci) and not missing(guci) then ci =
strip(strip(put(0.01*floor(glci/0.01),10.2)) || ', ' ||
strip(put(0.01*ceil(guci/0.01),10.2)));
run;

proc sort data=results04;
  by paramn trtan trta type avisitn avisit atptn atpt;
run;

proc sort data=blq1;
  by paramn trtan trta type avisitn avisit atptn atpt;
run;

data results05;
  merge results04 blq1;
  by paramn trtan trta type avisitn avisit atptn atpt;
  if type='abs' then aci='';
run;

proc sort data=results05;
  by type paramn avisitn avisit atptn atpt;
run;

proc transpose data=results05(where=(type='abs')) out=results06 prefix=r
name=varname;
  by paramn param avisitn avisit atptn atpt;
  var n meansd median minmax aci quart blq gmeancv ci;
  id trtan;
  idlabel trta;
run;

proc transpose data=results05(where=(type='pch' and avisitn>100))
out=results06c prefix=c name=varname;
  by paramn param avisitn avisit atptn atpt;
  var n meansd median minmax aci quart blq;
  id trtan;
  idlabel trta;

```

```

run;

proc sort data=results06;
  by paramn avisitn avisit atptn atpt varname;
run;

proc sort data=results06c;
  by paramn avisitn avisit atptn atpt varname;
run;

data results07;
  merge results06 results06c;
  by paramn avisitn avisit atptn atpt varname;
  attrib stat variable var2 length = $100.;
  varname=upcase(varname);

  if not missing(atpt) then variable=compbl(avisit ||', '|| atpt);
  else variable=compbl(avisit);

  if index(param,'creat') then do;
    var2='Concentration Adjusted for Creatinine ('||scan(param,2,'(')
;
    paramn=paramn+90;
  end;
  else do;
    var2='Quantity Excreted over 24 hours ('||scan(param,2,'(') ;
  end;

  if varname='N' then do;
    statord=1;
    stat='n';
  end;
  else if varname='BLQ' then do;
    statord=2;
    stat='BLOQ - n (%)';
    /*delete;*/ /*No BLQ values for this parameter*/
/* 4) JMH 25Sep2014 */
  end;
  else if varname='GMEANCV' then do;
    statord=3;
    stat='Geometric Mean (CV%)';
  end;
  else if varname='CI' then do;
    statord=4;
    stat='Geometric 95% CI';
  end;
  else if varname='MEDIAN' then do;
    statord=5;
    stat='Median';
  end;
  else if varname='QUART' then do;
    statord=6;
    stat='Q25, Q75';
  end;
end;

```

```

        else if varname='MINMAX' then do;
            statord=7;
            stat='Min, Max';
        end;
        else if varname='MEANSD' then do;
            statord=8;
            stat='Mean (SD)';
        end;
        else if varname='ACI' then do;
            statord=9;
            stat='95% CI';
        end;
        drop varname;
run;

data results08;
    set results07;

    if stat='n' then do;
        * havent set changes to missing as not expected ;
        if missing(r1) then r1='0';
        if missing(r2) then r2='0';
        if missing(r3) then r3='0';
    end;

    /* 5) JH 03OCT2014 - START */
    IF STAT = "BLOQ - n (%)" THEN DO;
        IF COMPRESS(R1) = "0" AND COMPRESS(C1) = "0" THEN C1 = "";
        IF COMPRESS(R2) = "0" AND COMPRESS(C2) = "0" THEN C2 = "";
        IF COMPRESS(R3) = "0" AND COMPRESS(C3) = "0" THEN C3 = "";
    END;
    /* 5) JH 03OCT2014 - END */

run;

data labels;
set results08;
    attrib r1 label = "Raw$value"
           r2 label = "Raw$value"
           r3 label = "Raw$value"
           c1 label = '%Change$ (*)'
           c2 label = '%Change$ (*)'
           c3 label = '%Change$ (*)';

    if index(variable,'T0') then
variable=tranwrd(variable,'T0','T${sub 0}');

    flag=1;
run;

proc sql noprint;
    create table table.T_15_02_04_30 as
    select paramn, var2, avisitn, atpt, variable, statord, stat, r1,
c1, r2, c2, r3, c3

```



```

        from labels
        order by paramn, var2, avisitn, atptn, statord;
quit;

proc sort data=labels;
    by paramn avisitn atptn statord;
run;

data paging;
    set labels;
    by paramn avisitn atptn statord;
    if (first.avisitn or first.atptn) or ln > 16 then ln=1; /*Amend to
look presentable, and avoid page overflows*/
    else ln+1;
    if ln=1 then page+1;
    call symput("page",compress(put(page,best.)));
run;

options number nodate orientation=landscape papersize=&p_pgsz missing='
';
ods escapechar='$';
%let linetop = \brdrt\brdrs\brdrw30; * needs to be 1.5pt so calculated
in twips (1/20 pt) ;
%let linebot = \brdrb\brdrs\brdrw30;

ods path stdlib.tl06324 (read) ;
ods results off;
ods rtf toc_data
file="/cvn/projects/prj/data/000000106324/TFL/&TFL_Part./&tflno..rtf"
style=tl06324 startpage=yes headery=1440 footery=1440 ;
ods noproctitle;

%let count=0;

%do j=1 %to 3; /*Will not fit nicely on 2 pages so changed to 3 - SBMA*/

%do i=1 %to &page;

%let count=%eval(&count+1);

%let totpage=%eval(&page*3);

title ;
footnote;
%let wd=0;

data comp;
    set paging end=eof;
    where page=&i;

    /* Amend title as needed */

```

```

    _firtitl="Table 15.2.4.30 Descriptive Statistics of Urinary S-BMA -
FAS";
    _upcas=(length("Path: &TFLpath.")-
length(compress("Path:&TFLpath.",'ABCDEFGHIJKLMNOPQRSTUVWXYZ')))/2;
    len=&blankn.-length("(page &count of &totpage)");
    if eof then do;
        call symput('_FSRTITL', trim(left(_firtitl)));
        call symput('_blankn', compress(put(len,best.)));
    end;

    drop _firtitl _upcas len;
run;

ods proclabel = ' ';
ods listing close;

* most set up in template others below;
* title arial 12pt bold with 12pt paragraph space below;
* all headers to be arial 11pt bold;
* data arial 10pt;
* headers to be central, text values left aligned and numeric centered
around decimal point;
proc report data = comp missing headline headskip missing nowd split =
'$' %if &i=1 %then %do; contents=' ' %end; %else %do; contents='' %end;;;
    column flag page paramn var2 avisitn atptn variable statord stat
    %if &j=1 %then %do; ("THS 2.2$(N=&trt1)&linebot" r1 c1) %end;
    %else %if &j=2 %then %do; ("CC$(N=&trt2)&linebot" r2 c2)%end;
    %else %do; ("SA$(N=&trt3)&linebot" r3 c3)%end;;

    define flag          / order order = internal noprint;
    define page          / order order = internal noprint;
    define paramn        / order order = internal noprint;
    define var2          / group style={just=left cellwidth=3cm}
style(header)={just=center} "Variable";
    define avisitn       / order order=internal noprint;
    define atptn        / order order=internal noprint;
    define variable      / group style={just=left cellwidth=1.5cm}
style(header)={just=center} "Timepoint";
    define statord       / order order = internal noprint;
    define stat         / display style={just=left cellwidth=3.1cm}
style(header)={just=center} "Statistic";
    %if &j=1 %then %do;
        define r1        / display style={just=center cellwidth=3cm}
style(header)={just=center};
        define c1        / display style={just=center cellwidth=3cm}
style(header)={just=center};
        %end;
    %else %if &j=2 %then %do;
        define r2        / display style={just=center cellwidth=3cm}
style(header)={just=center};
        define c2        / display style={just=center cellwidth=3cm}
style(header)={just=center};
    %end;
    %else %do;

```

```

        define r3                / display style={just=center cellwidth=3cm}
style(header)={just=center};
        define c3                / display style={just=center cellwidth=3cm}
style(header)={just=center};
        %end;

break before flag / page %if &i=1 %then %do;
contents="&_fsrtitl" %end; %else %do; contents='' %end;;

break after page / page;

compute after variable;
        line " ";
endcomp;

compute before page / style={protectspecialchars=off};
        line "&linetop";
endcomp;

compute before _page_ / style={just=left protectspecialchars=off};
        line "\b\fs24\sa24&_FSRTITL." ; * \b = bold, \fs24 is font
size 12pt, \sa24 is space after 12pt;
        line "&linebot";
endcomp;

compute after _page_ / style={just=left protectspecialchars=off
pretext="&linetop."};
        line 'Note: CC = Conventional cigarettes; SA = Smoking
abstinence; THS = Tobacco Heating System.';
        line 'Note: Geometric: mean, CV% and 95% confidence interval
(CI) are reported.';
        line "Note: * % change from baseline, where baseline is the
last assessment prior to first product use in CC/THS 2.2 arms on Day 1 or
last assessment prior to 06:29 AM in SA arm on Day 1."; /* 2) JR
18Sep2014 */
/*        line "Note: * % change from baseline, where baseline is
defined as the last assessment prior to 06:29 AM on Day 1.";*/
        line "Note: Collection over 24 hours starting on the Day stated in
the table.";
        %if &nsum. ge 1 %then %do;
                line "Note: BLOQ = number of observations imputed using half
limit of quantification (XX pg/mL).";
        %end;
        LINE "Note: No BLOQ values recorded for this parameter."; /* 4) JMH
25Sep2014 */
        line ' ';
        line 'Appendix 15.3.3.2';
        line "Path: &TFLpath." &_blankn.*"\~\~" "(Page &count of
&totpage)";
        line "Program Run: &sysdate &sysuserid Program Status:
&status";

```

```

        endcomp;
run;
%end;
%end;
ods rtf close;
ods results on;
ods path sashelp.tmplmst (read);

%mend ;

%outrtf(blankn=70, halfblnk=N);
ods listing;
proc printto print = "&table./T_15_02_04_30.lst" new;
run;

proc contents data = table.T_15_02_04_30 varnum;
run;
ods listing close;
proc printto ; run;
*=====;
* END OF PROGRAM CODE ;
*=====;

```