

```

%_mprintto;
options notes nosource;
proc datasets lib=work nolist memtype=data kill; quit;
%put NOTE:
=====;
%put NOTE: Covance Study Number : 000000106324;
%put NOTE: Client Protocol ID   : ZRHR-REXC-04-EU;
%put NOTE: Program Name        : t_conatc.sas;
%put NOTE: Purpose              : table of concomitant medication by ATC
classes;
%put NOTE: ;
%put NOTE: Input Data           : ADAM.ADCM;
%put NOTE: Output               : t_15_2_6_12_1(conatc);
%put NOTE: Macros Called        : _MPRINTTO;
%put NOTE: ;
%put NOTE: Programmed by        : cvn_jhardman;
%put NOTE: Creation Date        : 2014-07-28;
%put NOTE: SAS Version          : 9.3;
%put NOTE: ;
%put NOTE: == Latest Run
=====;
%put NOTE: Run by                : &sysuserid;
%put NOTE: Date/Time             :
%sysfunc(putn(%sysfunc(date()),e8601da.))T%sysfunc(putn(%sysfunc(time()),
e86011z.));
%put NOTE: ;
%put NOTE: == Modification History
=====;
%put NOTE: Date      Initials   No. Reason;
%put NOTE: 17Sep2014   JMH       1) Amended sorting;
%put NOTE: ;
%put NOTE:
=====;
options notes source source2 nofullstimer validvarname=upcase missing='
';
ods _all_ close;
ods listing;

*=====;
* START OF PROGRAM CODE                                     ;
*=====;

/* Standard - just change the number to match the listing you're working
on. Also change the letters in the*/
/* bracket, eg ccb = current cigarette brands. Make sure to do this at
the top of the code too. */

      %let tflno=T_15_02_06_12_01(conatc);

/* Standard - leave this */
%let TFL_Part=%scan(&_SASPROGRAMFILE,-3,%str(/));

/* Standard - leave this */
data _null_;

```

```

    tmp="&TFL_Part";
    if tmp not in ("dev" "qc") then call symput("TFL_Part", "prod");
    call symput('TFLpath', compress("&_SASPROGRAMFILE", ""));
run;

*****;
* read in data ;
*****;

data adsl;
    set adam.adsl;
    where saffl = 'Y';
    attrib headtext1 length =$200.
                headorder1 length=8.;

    if missing(trt01a) or trt01a='Screen failure' then delete;
    if index(trt01a,'Enroll') then do;
        trt01an=98;
        trt01a='Exposed not randomized';
    end;
    headorder1=trt01an;
    headtext1=trt01a;
    output;
    trt01an=99;
    headorder1=99;
    trt01a='Overall Safety';
    headtext1='Overall Safety';
    output;
run;

data dumtrts; /*Use this to output any columns for which N=0*/
    attrib headtext1 length =$200.
                headorder1 length=8.;

    headorder1=1;
    headtext1='THS 2.2';
    output;
    headorder1=2;
    headtext1='CC';
    output;
    headorder1=3;
    headtext1='SA';
    output;
    headorder1=98;
    headtext1='Exposed not randomized';
    output;
run;

proc freq data=adsl noprint;
    table headorder1*headtext1/ out =tot(drop=percent);
run;

data tot2;
    merge tot(in=a) dumtrts(in=b);

```

```

        by headorder1 headtext1;
        if b and not a then count=0;
        call symput('trt' || compress(put(headorder1,best.)),
compress(count));
run;

/*Now bring in CM data*/
data ae(drop=cmatc11 cmatc21);
    set adam.adcm(rename =(cmatc1=cmatc11 cmatc2=cmatc21));
    where saffl='Y' and anycmfl='Y' and cmfl='Y';
    attrib headtext1 length =$200.
                headorder1 length=8.
                cmatc1 length=$200.
                cmatc2 length=$200.;

    cmatc1=
left(trim(uppercase(substr(cmatc11,1,1))||lowercase(substr(cmatc11,2)))));
    cmatc2=
left(trim(uppercase(substr(cmatc21,1,1))||lowercase(substr(cmatc21,2)))));
    if missing(trta) or trta='Screen failure' then delete;
    if missing(cmatc1) then cmatc1='Missing';
    if index(trta,'Enroll') then do;
        trtan=98;
        trta='Exposed not randomized';
    end;
    headorder1=trtan;
    headtext1=trta;
    output;
    headorder1=99;
    headtext1='Overall Safety';
    output;
run;

proc sort data=ae; by headorder1 headtext1; run;

data adverse02;
    set ae;
run;

* Create an additional observation with missing VOL value for each table
section;
* This is used to ensure that all table rows are output, even for rows
with no adverse events;

data adverse03;
    set adverse02;
    output;
    cmatc1='Any medication';
    output;
run;

/** Number of Ae's overall **/
proc freq data=adverse03 noprint;
    tables headorder1*headtext1*cmatc1 / out=ovall(rename=(count=tot)
drop=percent);

```

```

run;

/** getting number of subjects studied ***/
proc sort data=adverse03 out=nae3 nodupkey;
  by headorder1 headtext1 cmatc1 subjidn;
run;

proc freq data=nae3 noprint;
  tables headorder1*headtext1*cmatc1/ out=novall(rename=(count=ntot)
drop=percent);
run;

data otot;
  merge oval1 novall;
  by headorder1 headtext1 cmatc1;
run;

/** number of subjects and aes in overall **/
data overall;
  set otot;
    if cmatc1='Any medication' then sort2=1;
    else sort2=2;
  sort3=0;
run;

data body2;
  set overall;
    if cmatc1='Any medication' then do; sort2=1; sort3=0; end;
    else do; sort2=2; sort3=0; end;
run;

/** bodysystem by prefterm **/
proc freq data=adverse03 noprint;
  tables headorder1*headtext1*cmatc1*cmatc2 /
out=preft(rename=(count=tot) drop=percent);
run;

/** getting number of subjects studied ***/
proc sort data=adverse03 out=npae2 nodupkey;
  by headorder1 headtext1 cmatc1 cmatc2 subjidn;
run;

proc freq data=npae2 noprint;
  tables headorder1*headtext1*cmatc1*cmatc2 /
out=npreftr(rename=(count=ntot) drop=percent);
run;

data prefterm;
  merge preft npreftr;
  by headorder1 headtext1 cmatc1 cmatc2;
run;

data cmatc2;
  set prefterm;

```

```

        if cmatc1='Any medication' then do; sort2=1; sort3=0; end;
    else do; sort2=2; sort3=1; end;
run;

/*Set together the body systems on their own, and the body systems with
preferred terms*/
data all;
    set overall cmatc2;
run;

proc sort data=all out=all2;
    by headorder1 headtext1 sort2 cmatc1 cmatc2;
run;

data format;
    merge all2(in=a) dumtrts tot;
    by headorder1 headtext1;
        if not a then do;
            sort2=1;
            sort3=0;
            cmatc1='Any medication';
        end;
run;

data format2;
    set format;
    attrib text text2 text3 format=$200.;
    /* Percentage of subjects*/
    if not missing(count) then percent=put((ntot/count)*100,8.1);
    else percent='0';

    /* display variables*/

        /*          else text=put(ntot,3.)||'
('||compress(put(percent,8.1))||')';*/

        /*n value*/
        if missing(ntot) then text='0';
        else text=put(ntot,3.);

        /*% value*/
        if missing(percent) then text3='';
        else if percent=100 then text3='(100  %)';
        else if percent ge 10 then text3='(
'||compress(put(percent,8.1))||'%)';
        else if percent lt 10 then text3='(
'||compress(put(percent,8.1))||'%)';

        /*events value*/
        if missing(tot) then text2='';
        else text2=compress(put(tot,3.));

```

```

        if cmatc1='Any medication' and not missing(cmatc2) then
delete;
        drop percent;
run;

proc sort data=format2 nodupkey; by headorder1 headtext1 cmatc1 tot
ntot sort2 sort3 cmatc2 count text text3 text2; run;

proc sort data=format2; by headorder1 headtext1 sort2 cmatc1 sort3
cmatc2; run;

proc sort data=format2 out=format3; by sort2 cmatc1 sort3 cmatc2; run;

/*Transpose n values*/
proc transpose data=format3 out=nformat prefix=n;
  by sort2 cmatc1 sort3 cmatc2;
  var text;
  id headorder1;
  idlabel headtext1;
run;

/*Transpose % values*/
proc transpose data=format3 out=performat prefix=p;
  by sort2 cmatc1 sort3 cmatc2;
  var text3;
  id headorder1;
  idlabel headtext1;
run;

/*Transpose event values*/
proc transpose data=format3 out=eformat prefix=e;
  by sort2 cmatc1 sort3 cmatc2;
  var text2;
  id headorder1;
  idlabel headtext1;
run;

data tformat;
  merge nformat eformat performat;
  by sort2 cmatc1 sort3 cmatc2;
run;

data tsort2;
  set tformat;
  n99n=input(n99,8.);
  e99n=input(e99,8.);*/
/*
E99N=INPUT(E99,8.); /* 1) JMH 17Sep2014 */
run;

proc sort data=tsort2 out=allsorts;
  by sort2 sort3 descending n99n descending e99n cmatc1;
run;

```

```

/* Create a variable to sort body systems by most frequent - ODD*/
data sorting;
  set allsorts(where=(sort2=2 and sort3=0) keep=sort2 cmatc1 sort3 n99n
e99n);
  by sort2 sort3 descending n99n descending e99n cmatc1;
  if first.cmatc1 then odd+1;
  keep sort2 cmatc1 odd;
run;

/*Merge this back onto data so that ODD (the ordering variable for body
systems) is merged onto all preferred terms*/
proc sort data=allsorts; by sort2 cmatc1; run;
proc sort data=sorting; by sort2 cmatc1; run;

data sorting2;
  merge sorting allsorts;
  by sort2 cmatc1;
run;

proc sort data=sorting2;
  by sort2 odd sort3 descending n99n descending e99n cmatc2;
run;

/*Now create a variable to sort preferred terms within each body system
by most frequent - ODD2*/
data sorting3;
  set sorting2(where=(sort2=2 and sort3=1) keep=sort2 cmatc1 odd sort3
cmatc2 n99n e99n);
  by sort2 odd sort3 descending n99n descending e99n cmatc2;
  if first.cmatc2 then odd2+1;
  keep sort2 cmatc1 odd sort3 cmatc2 odd2;
run;

/*Merge this back onto data so that ODD2 can be used to order the
preferred terms within body systems*/
proc sort data=sorting2; by sort2 odd cmatc1 sort3 cmatc2; run;
proc sort data=sorting3; by sort2 odd cmatc1 sort3 cmatc2; run;

data sorting4;
  merge sorting2 sorting3;
  by sort2 odd cmatc1 sort3 cmatc2;
run;

proc sort data=sorting4 out=final;
  by sort2 odd sort3 odd2;
run;

data final2;
  set final;
  attrib column format=$200. label='Formatted text'
        column2 format=$200. label='Unformatted text';

/*Create indents as required in output*/
attrib wrap length = $200;

```

```

wrap = cmatc2;

i=26; *This is the max length allowed on a single line - change as
needed;
if length(wrap)>i then do;
  nwraps = int(length(wrap)/i); *Calculate how many lines the text will
  wrap over;
  do while(nwraps > 0);
    fin=0;
    j = i*nwraps; *Calculate starting point - loop will cycle backwards
    from this point looking for a space;
    do while(fin=0 and j gt 1);
      if substr(wrap,j,1)=' ' then do;
        wrap=substR(wrap,1,j-1) || "|n |S={foreground=white} . |S={} " ||
substr(wrap,j+1);
        fin=1;
      end;
      else j=j-1; *No space found - move back one character;
    end;
    nwraps=nwraps-1; *Once this wrap is handled, move up a line until all
    are handled (when nwraps = 0);
  end;
end;

if sort3=1 then column2 = cmatc2;
if sort2=2 and sort3=0 then column2=trim(cmatc1);
if sort2=1 then do; column2='Any medication'; odd2=0; end;

if sort3=1 then column = "|S={foreground=white} . |S={} " || wrap ;
if sort2=2 and sort3=0 then column=trim(cmatc1);
if sort2=1 then do; column='Any medication'; odd2=0; end;

run;

/*Create code to set flags so we know which values should be set to blank
in the output*/
proc sort data=final2(where=(sort3=0)) out=blanks;
  by sort2 sort3;
run;

data blanks1;
  set blanks;
  if (n1=0 or missing(n1)) and (e1=0 or missing(e1)) then
del1=1;
  if (n2=0 or missing(n2)) and (e2=0 or missing(e2)) then
del2=1;
  if (n3=0 or missing(n3)) and (e3=0 or missing(e3)) then
del3=1;
  if (n98=0 or missing(n98)) and (e98=0 or missing(e98)) then
del98=1;
  keep sort2 sort3 cmatc1 del;;
run;

proc sort data=final2; by sort2 cmatc1; run;

```



```

proc sort data=blanks1; by sort2 cmatc1; run;

data final3;
    merge final2 blanks1;
    by sort2 cmatc1;
run;

proc sort data=final3;
    by sort2 odd cmatc1 sort3 odd2 ;
run;

data labels;
    set final3;
attrib n1 label = " n"

                                n2 label = " n"
                                n3 label = " n"
                                n98 label = " n"
                                n99 label = " n"
                                p1 label = ' (%) '
                                p2 label = ' (%) '
                                p3 label = ' (%) '
                                p98 label = ' (%) '
                                p99 label = ' (%) '
                                e1 label = "Events"
                                e2 label = "Events"
                                e3 label = "Events"
                                e98 label = "Events"
                                e99 label = "Events";

    if sort3=0 then do; /*Zero still wants to be displayed for body
system as this is hte top level*/
        del1=.;
        del2=.;
        del3=.;
        del98=.;
    end;
run;

data final4;
    set labels;

    array a [5] n1 n2 n3 n98 n99;
        array b [5] del1 del2 del3 del98 del99;
    array c [5] e1 e2 e3 e98 e99;
    do i=1 to 5;
        if b[i] ne 1 then do;
            if missing(a[i]) then a[i] ='0';
        end;
        if length(left(strip(c[i])))=2 then c[i]=
'|S={foreground=white} .|S={} ' || left(strip(c[i]));
        if length(left(strip(c[i])))=1 then c[i]=
'|S={foreground=white} .|S={} ' || left(strip(c[i]));
    end;

```

```

flag=1;

run;

proc sql noprint;
    create table table.T_15_02_06_12_01 as
        select column, column2, n1, p1, e1, n2, p2, e2, n3, p3, e3, n98,
p98, e98, n99, p99, e99
        from final4
        order by sort2, odd, cmatc1, sort3, odd2;
quit;

data paging;
    set final4;
    by sort2 odd cmatc1 sort3 odd2;
    if (ln gt 8 and first.odd) or ln gt 10 then ln=1;
    else ln+1;

    if ln=1 then page+1;
    call symput("page",compress(put(page,best.)));

    retain sort4;
    if first.cmatc1 then sort4+1;
run;

/* Standard - leave this */
options nonumber nodate orientation=landscape papersize=&p_pgsz
missing=' ';
ods escapechar='|';
%let linetop = \brdrt\brdrs\brdrw30; * needs to be 1.5pt so calculated
in twips (1/20 pt) ;
%let linebot = \brdrb\brdrs\brdrw30;
/* Standard - macro for paging */
%macro outrtf(blankn=70, halfblnk=N);

%if &halfblnk=N %then %let halfblnk=;
%else %if &halfblnk=Y %then %let halfblnk=\~;

ods path stdlib.tl06324 (read) ;
ods results off;
ods rtf toc_data/* contents*/
file="/cvn/projects/prj/data/000000106324/TFL/&TFL_Part./&tflno..rtf"
style=tl06324 startpage=yes headery=1440 footery=1440 ;
ods noproctitle;
%do i=1 %to &page;

title ;
footnote;
%let wd=0;
ods proclabel = ' ';

```

```

data comp;
    set paging end=eof;
    where page=&i;

    /* Amend title as needed */
    _firtitl="Table 15.2.6.12.1 Summary of Concomitant
Medication by Anatomical Therapeutic Classes (ATC) 1 and 2 -";
    _upcas=(length("Path: &TFLpath.")-
length(compress("Path:&TFLpath.",'ABCDEFGHIJKLMNOPQRSTUVWXYZ')))/2;
    len=&blankn.-length("(Page &i of &page)");
    if eof then do;
        call symput('_FSRTITL', trim(left(_firtitl)));
        call symput('_blankn', compress(put(len,best.)));
    end;
    drop _firtitl _upcas len;
run;

ods listing close;

* most set up in template others below;
* title arial 12pt bold with 12pt paragraph space below;
* all headers to be arial 11pt bold;
* data arial 10pt;
* headers to be central, text values left aligned and numeric centered
around decimal point;
/* Update with your variables as needed */
proc report data = comp headline headskip missing nowd split = '$' %if
&i=1 %then %do; contents=' ' %end; %else %do; contents='' %end;;
column flag page sort2 odd sort4 sort3 odd2 ("ATC1" column) ("THS 2.2
$(N=&trt1) &linebot" n1 p1 e1) ("CC$(N=&trt2) &linebot" n2 p2 e2)

        ("SA $(N=&trt3) &linebot" n3 p3 e3) ("Exposed
Not$Randomized$(N=&trt98) &linebot" n98 p98 e98)

        ("Overall$Safety$(N=&trt99) &linebot" n99 p99 e99); ;
define flag          / order order = internal noprint;
define page          / order order = internal noprint;
define sort2         / order order=internal noprint;
define odd           / order order=internal noprint;
define sort4         / order order=internal noprint;
define sort3         / order order=internal noprint;
define odd2          / order order=internal noprint;

        define column / group style={just=left cellwidth=4cm}
style(header)={just=center} "| \~ ATC2";
        define n1          / display style={just=d cellwidth=0.5cm}
style(header)={just=right} ;
        define p1          / display style={just=d cellwidth=1.2cm}
style(header)={just=center} ;
        define e1          / display
style={JUST=left cellwidth=1.2cm} style(header)={just=l} ;

```

```

        define n2                / display style={just=d cellwidth=0.5cm}
style(header)={just=right} ;
        define p2                / display style={just=d cellwidth=1.2cm}
style(header)={just=center} ;
        define e2                / display style={just=left
cellwidth=1.2cm } style(header)={just=l} ;
        define n3                / display style={just=d cellwidth=0.5cm}
style(header)={just=right} ;
        define p3                / display style={just=d cellwidth=1.2cm}
style(header)={just=center} ;
        define e3                / display
style={just=left cellwidth=1.2cm} style(header)={just=l} ;
        define n98               / display style={just=d cellwidth=0.5cm}
style(header)={just=right} ;
        define p98               / display style={just=c cellwidth=1.2cm}
style(header)={just=center} ;
        define e98               / display style={just=left
cellwidth=1.2cm} style(header)={just=l} ;
        define n99               / display style={just=d cellwidth=0.5cm}
style(header)={just=right} ;
        define p99               / display style={just=d cellwidth=1.2cm}
style(header)={just=center} ;
        define e99               / display style={JUST=left
cellwidth=1.2cm} style(header)={just=l} ;

```

```

break before flag / page %if &i=1 %then %do;
contents("&_fsrtitl" %end; %else %do; contents='' %end;;

```

```

break after page / page;

```

```

compute after sort4;
    line " ";
endcomp;

```

```

compute before page / style={protectspecialchars=off};
    line "&linetop";
endcomp;

```

```

    compute before _page_ / style={just=left protectspecialchars=off};
        line "\b\fs24\sa24&_FSRTITL." ; * \b = bold, \fs24 is font
size 12pt, \sa24 is space after 12pt;
        line "\b\fs24\sa24Safety Population";
        line "&linebot";
    endcomp;

```

```

    compute after _page_ / style={just=left protectspecialchars=off
pretext="&linetop."};
        line 'Note: CC = Conventional cigarettes; SA = Smoking
abstinence; THS = Tobacco Heating System.';
        LINE 'Note: Exposed Not Randomized refers to all subjects
exposed to THS 2.2 but not randomized. Overall Safety refers to all
subjects exposed to THS 2.2.';

```

```

        line 'Note: Percentages are based on the number of subjects
indicated in the column header (N).';
        line ' ';
        line 'Appendix 15.3.6.3.2';
        line "Path: &TFLpath." &_blankn.*"\~\~" "(Page &i of &page)";
;
        line "Program Run: &sysdate   &sysuserid   Program Status:
&status";
        endcomp;

run;
%end;
ods rtf close;
ods results on;
ods path sashelp.tmplmst (read);

%mend ;

%outrtf(blankn=70, halfblnk=N);
ods listing;
proc printto print = "&table./T_15_02_06_12_01.lst" new;
run;

proc contents data = table.T_15_02_06_12_01 varnum;
run;
ods listing close;

proc printto ; run;
*=====;
* END OF PROGRAM CODE ;
*=====;

```