

```

%_mprintto;
options notes nosource;
proc datasets lib=work nolist memtype=data kill; quit;
%put NOTE:
=====;
%put NOTE: Covance Study Number : 000000106326;
%put NOTE: Client Protocol ID   : ZRHM-PK-05-JP;
%put NOTE: Program Name        : t_qsu.sas;
%put NOTE: Purpose              : table of QSU factors and total score;
%put NOTE: ;
%put NOTE: Input Data           : ADAM.ADSL ADAM.ADQSSU;
%put NOTE: Output               : t_15_2_4_14(qsu);
%put NOTE: Macros Called        : _MPRINTTO;
%put NOTE: ;
%put NOTE: Programmed by        : cvn_jriley;
%put NOTE: Creation Date        : 2014-08-06;
%put NOTE: SAS Version          : 9.3;
%put NOTE: ;
%put NOTE: == Latest Run
=====;
%put NOTE: Run by                : &sysuserid;
%put NOTE: Date/Time             :
%sysfunc(putn(%sysfunc(date()),e8601da.))T%sysfunc(putn(%sysfunc(time()),
e86011z.));
%put NOTE: ;
%put NOTE: == Modification History
=====;
%put NOTE: Date      Initials   No. Reason;
%put NOTE: 11Aug2014   JR        1) Amended footnote;
%put NOTE: 23Sep2014   JR        2) Added QSU footnote;
%put NOTE: ;
%put NOTE:
=====;
options notes source source2 nofullstimer validvarname=upcase missing='
';
ods _all_ close;
ods listing;

*=====;
* START OF PROGRAM CODE                                     ;
*=====;

%let tflno=T_15_02_04_14(qsu);

%let TFL_Part=%scan(&_SASPROGRAMFILE,-3,%str(/));

data _null_;
  tmp="&TFL_Part";
  if tmp not in ("dev" "qc") then call symput("TFL_Part", "prod");
  call symput('TFLpath', compress("&_SASPROGRAMFILE", ""));
run;

*****;

```

```

* read in data ;
*****;

/* Calculate totals for products */
data adsl;
    set adam.adsl(where=(pprotfl='Y'));
    if analgrln=1 then do;
        if index(trt01a,'THS 2.2') or index(trt02a,'THS 2.2') then
trtord=1;
        output;
        if index(trt01a,'CC') or index(trt02a,'CC') then trtord=2;
        output;
    end;
    else if analgrln=2 then do;
        if index(trt01a,'THS 2.2') or index(trt02a,'THS 2.2') then
trtord=10;
        output;
        if index(trt01a,'NRT gum') or index(trt02a,'NRT gum') then
trtord=7;
        output;
    end;
    else if missing(analgrln) then delete;
run;

proc sort data=adsl nodupkey out=adsl1;
    by analgrln analgr1 trtord subjid;
run;

proc freq data=adsl1(where=(not missing(trtord))) noprint;
    table analgrln*analgr1*trtord/ out =totals2(drop=percent
rename=(count=total));
run;

data totals3;
    set totals2;

    call symput('trt'||strip(put(trtord,best.)),strip(put(total,best.)));
run;

proc sort data=totals3;
    by analgrln analgr1 trtord;
run;

/*Bring in appropriate data from ADQSSU*/
data adqssu;
    set adam.adqssu(where=(anl01fl='Y' and pprotfl='Y'));
run;

data adqssu_orig;
    set adqssu;

    statval=aval;

    if atpt='T0 + 15 min' or atpt='T0 + 20 min' then do;

```

```

        atpt='T0 + 15/20 min';
        atptn=6;
    end;
run;

proc sort data=adqssu_orig;
    by analgr1n analgr1 trtan trta parcat2n parcat2 paramn param paramcd
    atptn atpt;
run;

proc means data=adqssu_orig alpha=0.05 noprint;
    var statval;
    by analgr1n analgr1 trtan trta parcat2n parcat2 paramn param paramcd
    atptn atpt;
    output out=results02 n=n1 mean=mean1 std=std1 median=median1 min=min1
    max=max1 q1=q1 q3=q3 lclm=lci1 uclm=uci1;
run;

data results03;
    set results02;
    attrib meansd length=$20.
        minmax length=$20.
        n length=$20.
        median length=$20.
        ci length=$20.
        quart length=$20.;

    n = left(compress(put(n1,8.)));
    if not missing(median1) then median =
left(compress(put(median1,8.2)));
    if not missing(mean1) and not missing(std1) then meansd =
left(compress(put(round(mean1,0.01),8.2))) || ' (' ||
left(compress(put(0.001*ceil(std1/0.001),8.3))) || ')';
    if not missing(min1) and not missing(max1) then minmax =
left(compress(put(min1,8.1))) || ', ' || left(compress(put(max1,8.1)));
    if not missing(lci1) and not missing(uci1) then ci =
strip(strip(compress(put(0.01*floor(lci1/0.01),8.2)))) || ', ' ||
strip(compress(put(0.01*ceil(uci1/0.01),8.2)));
    if not missing(q1) and not missing(q3) then quart =
strip(strip(put(q1,8.2)) || ', ' || strip(put(q3,8.2)));

    drop n1 mean1 std1 median1 min1 max1 lci1 uci1 q1 q3;
run;

data results04; /*Create text as required in output*/
    set results03;
    attrib paramc length = $100.;

    if index(parcat2,'Factor')=0 then paramc=strip(param);
    else paramc=strip(parcat2);

    if analgr1n=2 and trtan=4 then trtan=10;

    drop param paramcd parcat2 parcat2n;

```

```

run;

proc sort data=results04;
    by paramn paramc atptn atpt;
run;

proc transpose data=results04 out=results05 prefix=_ name=varname;
    by paramn paramc atptn atpt;
    var n meansd median minmax ci quart;
    id trtan;
    idlabel trta;
run;

data results06;
    set results05;
    attrib stat length = $100.;

    if varname='N' then do;
        statord=1;
        stat='n';
    end;
    else if varname='MEANSD' then do;
        statord=2;
        stat='Mean (SD)';
    end;
    else if varname='CI' then do;
        statord=3;
        stat='95% CI';
    end;
    else if varname='MEDIAN' then do;
        statord=4;
        stat='Median';
    end;
    else if varname='QUART' then do;
        statord=5;
        stat='Q25, Q75';
    end;
    else if varname='MINMAX' then do;
        statord=6;
        stat='Min, Max';
    end;

    drop varname;
run;

data results07;
    set results06;

    if stat='n' then do;
        if missing(_4) then _4='0';
        if missing(_5) then _2='0';
        if missing(_10) then _10='0';
        if missing(_7) then _7='0';
    end;

```

```

run;

data labels;
set results07;
  attrib _4 label = "THS 2.2 Menthol$(N=&trt1)"
         _5 label = "mCC$(N=&trt2)"
         _10 label = "THS 2.2 Menthol$(N=&trt10)"
         _7 label = "NRT gum$(N=&trt7)"
         ATPT label= "Unformatted timepoint";

  if not index(paramc,'-') then
paramc=upcase(substr(paramc,1,1))||lowercase(substr(paramc,2));
  if index(atpt,'T0') then atpt=tranwrd(atpt,'T0','T${sub 0}');
run;

proc sort data=labels;
  by paramn atptn statord;
run;

/*options replace;*/
proc sql noprint;

create table table.t_15_02_04_15 as
select paramc, atpt, stat, _4, _5, _10, _7
from labels
order by paramn, atptn, statord;

quit;
/*options noreplace;*/

data paging;
  set labels;
  by paramn atptn statord;

  flag=1;

  if ln gt 11 then ln=1; /*Amend to look presentable, and avoid page
overflows*/
  else ln+1;
  if ln=1 then page+1;
  call symput("page",compress(put(page,best.)));
run;

options number nodate orientation=landscape papersize=&p_pgsz missing='
';
ods escapechar='$';
%let linetop = \brdrt\brdrs\brdrw30; * needs to be 1.5pt so calculated
in twips (1/20 pt) ;
%let linebot = \brdrb\brdrs\brdrw30;
%macro outrtf(blankn=, halfblnk=);

%if &halfblnk=N %then %let halfblnk=;

```

```

%else %if &halfblnk=Y %then %let halfblnk=\~;

ods path stdlib.tl06326 (read) ;
ods results off;
ods rtf toc_data
file="/cvn/projects/prj/data/000000106326/TFL/&TFL_Part./&tflno..rtf"
style=tl06326 startpage=yes headery=1440 footery=1440 ;
ods noproctitle;
%do i=1 %to &page;

title ;
footnote;
%let wd=0;
ods proclabel=' ';

data comp;
    set paging end=eof;
    where page=&i;

    /* Amend title as needed */
    _firtitl="Table 15.2.4.14 Descriptive Statistics of QSU-brief
Questionnaire Factors and Total Score - PK Population";
    _upcas=(length("Path: &TFLpath.")-
length(compress("Path:&TFLpath.",'ABCDEFGHIJKLMNOPQRSTUVWXYZ')))/2;
    len=&blankn.-length("(page &i of &page)");
    if eof then do;
        call symput('_FSRTITL', trim(left(_firtitl)));
        call symput('_blankn', compress(put(len,best.)));
    end;
    drop _firtitl _upcas len;
run;

ods listing close;

* most set up in template others below;
* title arial 12pt bold with 12pt paragraph space below;
* all headers to be arial 11pt bold;
* data arial 10pt;
* headers to be central, text values left aligned and numeric centered
around decimal point;
proc report data = comp missing headline headskip missing nowd split =
'$' %if &i=1 %then %do; contents=' ' %end; %else %do; contents='' %end;;
;
    column flag page paramn paramc atptn atpt statord stat ("Group-1 PK
&LINEBOT" _4 _5) ("Group-2 PK &LINEBOT" _10 _7);

    define flag          / order order=internal noprint;
    define page          / order order = internal noprint;
    define paramn        / order order = internal noprint;

```

```

        define paramc          / group style={just=left cellwidth=2cm}
style(header)={just=center} "Variable";
        define atptn          / order order=internal noprint;
        define atpt           / group style={just=left cellwidth=1.5cm}
style(header)={just=center} "Timepoint";
        define statord        / order order = internal noprint;
        define stat           / display style={just=left cellwidth=1.5cm}
style(header)={just=center} "Statistic";
        define _4             / display style={just=c cellwidth=1.5cm}
style(header)={just=center};
        define _5             / display style={just=c cellwidth=1.5cm}
style(header)={just=center};
        define _10            / display style={just=c cellwidth=1.5cm}
style(header)={just=center};
        define _7             / display style={just=c cellwidth=1.5cm}
style(header)={just=center};

break before flag / page %if &i=1 %then %do;
contents="&_fsrtitl" %end; %else %do; contents='' %end;;

break after page / page;

compute after atptn;
    line " ";
endcomp;

compute before page / style={protectspecialchars=off};;
    line "&linetop";
endcomp;

compute before _page_ / style={just=left protectspecialchars=off};
    line "\b\fs24\sa24&_FSRTITL." ; * \b = bold, \fs24 is font
size 12pt, \sa24 is space after 12pt;
    line "&linebot";
endcomp;

compute after _page_ / style={just=left protectspecialchars=off
PRETEXT="&LINETOP."};
    line 'Note: mCC = menthol conventional cigarettes; NRT gum =
Nicotine Replacement Therapy gum; THS = Tobacco Heating System.';
    line "Note: T${sub 0} = Time of first product use at single
use day."; /* 1) JR 11Aug2014 */
/*
line "Note: T${sub 0} = Time of first product use at single
use day";*/
    line "Note: The QSU-brief values at T${sub 0} + 15/20 min
refer to QSU-brief data at time T${sub 0} + 15 min for THS 2.2 Menthol
and mCC, and to QSU-brief data at time T${sub 0} + 20 min for NRT gum.";
    LINE 'Note: QSU-brief scores reported on a 7-point scale.
Higher scores indicate greater intensity of urge.'; /* 2) JR 23Sep2014 */
    line ' ';
    line 'Appendix 15.3.6.11';
    line "Path: &TFLpath." &_blankn.*"\~\~" "(Page &i of &page)";
    line "Program Run: &sysdate &sysuserid Program Status:
&status";

```

```

        endcomp;
run;
%end;
ods rtf close;
ods results on;
ods path sashelp.tmplmst (read);

%mend ;

%outrtf(blankn=70, halfblnk=N);

ods listing;
proc printto print = "&table./t_15_02_04_15.lst" new;
run;

proc contents data = table.t_15_02_04_15 varnum;
run;
ods listing close;

proc printto ; run;
*=====;
* END OF PROGRAM CODE ;
*=====;

```