

```

%_mprintto;
options notes nosource;
proc datasets lib=work nolist memtype=data kill; quit;
/* Standard - leave this */
%let TFL_Part=%scan(&_SASPROGRAMFILE,-3,%str(/));

/* Standard - leave this */
data _null_;
    tmp="%TFL_Part";
    if tmp not in ("dev" "qc") then call symput("TFL_Part", "prod");
    call symput('TFLpath', compress("&_SASPROGRAMFILE",""));
run;
%put NOTE:
=====;
%put NOTE: Covance Study Number : 000000106326;
%put NOTE: Client Protocol ID   : ZRHR-PK-05-JP;
%put NOTE: Program Name        : tl_anlpk442.sas;
%put NOTE: Purpose              : table of sensitivity analysis PK data
for zero second imputation;
%put NOTE: ;
%put NOTE: Input Data           : ADAM.ADPP;
%put NOTE: Output               : L_15_04_04_02(PK) T_15_02_04_02(PK) ;
%put NOTE: Macros Called        : _MPRINTTO;
%put NOTE: ;
%put NOTE: Programmed by        : cvn_ahedge;
%put NOTE: Creation Date        : 2014-23-09;
%put NOTE: SAS Version          : 9.3;
%put NOTE: ;
%put NOTE: == Latest Run
=====;
%put NOTE: Run by                : &sysuserid;
%put NOTE: Date/Time             :
%sysfunc(putn(%sysfunc(date()),e8601da.))T%sysfunc(putn(%sysfunc(time()),
e86011z.));
%put NOTE: ;
%put NOTE: == Modification History
=====;
%put NOTE: Date          Initials    No. Reason;
%put NOTE: ;
%put NOTE: ;
%put NOTE: ;
%put NOTE:
=====;
options notes source source2 nofullstimer validvarname=upcase missing=' '
NOQUOTELNMAX/*turn off warnings about quoted strings to long*/;;
ods _all_ close;
ods listing;

/*formats macro and appendix output macros*/
%include
"/cvn/projects/prj/development/000000106326/dev/adhoc/TMPLTMIX.sas";

*=====;
* START OF PROGRAM CODE                                     ;
*=====;

```

```

/* Calculate totals for products */

data adsl;
  set adam.adsl(where=(pprotfl='Y'));
  if analgrln=1 then do;
    if index(trt01a,'THS 2.2') or index(trt02a,'THS 2.2') then
colord=1;
    output;
    if index(trt01a,'CC') or index(trt02a,'CC') then colord=2;
    output;
  end;
  else if analgrln=2 then do;
    if index(trt01a,'THS 2.2') or index(trt02a,'THS 2.2') then
colord=1;
    output;
    if index(trt01a,'NRT') or index(trt02a,'NRT') then colord=2;
    output;
  end;
  else if missing(analgrln) then delete;
run;

proc sort data=adsl nodupkey out=adsl1;
  by analgrln analgr1 colord subjid;
run;

proc freq data=adsl1(where=(not missing(colord))) noprint;
  table analgrln*analgr1*colord/ out =totals2(drop=percent
rename=(count=total));
run;

data _null_;
  set totals2;
  call
symput('tot'||strip(put(colord,best.))||strip(put(analgrln,best.)),strip(
put(total,best.)));
run;

*****;
* read in data ;
*****;
proc sort data=adam.adpp(where=(
paramcd in ('TMAX') /*cmax to count excluded subjects*/
and aval not in (.,0) and crit3fl ne 'Y' AND pprotfl='Y'))
  out=adpp;
  by subjid paramcd;
run;

proc sql;
create table adpp1 as
select *, count(distinct trtan) as trtcount
from adpp
group by analgrln, paramcd, subjid

```

```
order by subjid;  
quit;
```

```
/* take logs and exclude subjects with <2 timepoints*/
```

```
data adpp2 noanal;  
  attrib treat length=$7;  
  set adpp1;  
  if paramcd='TMAX' then param=tranwrd(strip(tranwrd(param,'max','`{sub  
max}')), 'T', 't');  
  else delete;  
  treat=trta;  
  if trtcount>1 then do;  
    logaval=log(aval);  
    output adpp2;  
  end;  
  else output noanal;  
run;
```

```
%fmt(datain=adpp2, start=paramn, label=param, name=param);
```

```
title1 j=1 "PAGESPLIT"; /*do not change*/
```

```
%let tflno=L_15_04_04_02(PK);
```

```
%mixout1(fileout=/cvn/projects/prj/data/000000106326/TFL/&TFL_Part./&tflno  
o);  
options ps=28;
```

```
data pk;  
set adam.adpp(where=(paramcd in ('TMAX' 'AUCIFO' 'AUCINT' 'AUCLST' 'CMAX'  
'LAMZHL') and anl01fl='Y' and pprotfl='Y'));  
if crit3fl='Y' and paramcd in ('AUCIFO' 'LAMZHL') then aval=.;  
run;
```

```
proc sort data=pk; by param analgr1 usubjid; run;
```

```
proc transpose data=pk out=tpk;  
by param analgr1 usubjid;  
var aval;  
id aperiod;  
run;
```

```
data tpk2(drop=_1 _2);  
set tpk;  
aperiod=1;  
aval=input(_1, best.);  
output;  
aperiod=2;  
aval=input(_2, best.);  
output;  
run;
```

```

data tpk2;
set tpk2;
if missing(aval) then missing='Yes';
else missing='No';
run;

proc sort data=tpk2; by analgr1; run;

title2 "Analysis group: #byvall1";

proc freq data=tpk2;
by analgr1;
table param*missing / crosslist nocol nopercent;
run;

%mixout2(blankn=70, halfblnk=Y,title=Listing 15.4.4.4.2 Analysis of
Pharmacokinetic Parameters of Nicotine Where >20% Missing Observations);

proc printto ; run;

/* create null dataset for output */
data ttabout;
analgrln=1;
param='      ';
stat='      ';
col1='      ';
col2='      ';
col3='      ';
output;
analgrln=2;
param='      ';
stat='      ';
col1='      ';
col2='      ';
col3='      ';
output;
run;

/* Standard - macro for paging */
%macro outrtf(blankn=68, halfblnk=N, ref=);

/* treatment column headers and footnotes */
/*group 1*/
%let col11=THS 2.2 Menthol# (N=&tot11);
%let col21=mCC# (N=&tot21);
%let col31=THS 2.2 Menthol:mCC#Ratio (%);
%let foot1=%str(mCC = menthol conventional cigarettes);
%let foot11=mCC;

/*group 2*/
%let col12=THS 2.2 Menthol# (N=&tot12);
%let col22=NRT gum# (N=&tot22);

```

```

%let col32=THS 2.2 Menthol#:NRT gum Ratio (%);
%let foot2=%str(NRT gum = Nicotine Replacement Therapy gum);
%let foot12=NRT gum;

%if &halfblnk=N %then %let halfblnk=;
%else %if &halfblnk=Y %then %let halfblnk=~;

/* Standard - just change the number to match the listing you're working
on. Also change the letters in the*/
/* bracket, eg ccb = current cigarette brands. Make sure to do this at
the top of the code too. */

%let tflno=T_15_02_04_02(PK);

/* Standard - leave this */
%let TFL_Part=%scan(&_SASPROGRAMFILE,-3,%str(/));

/* Standard - leave this */
data _null_;
    tmp="%TFL_Part";
    if tmp not in ("dev" "qc") then call symput("TFL_Part", "prod");
    call symput('TFLpath', compress("&_SASPROGRAMFILE",""));
run;

/*page numbers*/
data paging;
    set ttabout;
    by analgrln param ;
    flag=1;
    retain ln 0 page 0;
    if first.param then ln+1;
    if first.analgrln or ln>3 then do;
        page+1;
        ln=1;
    end;
    if last.analgrln then call symput("tpage",compress(put(page,best.)));
run;

/* Standard - leave this */
options number nodate orientation=landscape papersize=&p_pgsize missing='
' NOQUOTELENMAX/*turn off warnings about quoted strings to long*/;
ods escapechar='`';
%let linetop = \brdrt\brdrs\brdrw30; * needs to be 1.5pt so calculated
in twips (1/20 pt) ;
%let linebot = \brdrb\brdrs\brdrw30;
%let linebot2 = \brdrb\brdrs\brdrw15;

ods path stdlib.tl06326 (read) ;
ods results off;

```

```

ods rtf toc_data/* contents*/
file="/cvn/projects/prj/data/000000106326/TFL/&TFL_Part./&tflno..rtf"
style=t106326 startpage=yes headery=1440 footery=1440 ;
ods noproctitle;

%do i=1 %to &tpage;

ODS PROCLABEL = ' ';
title ;
footnote;
%let wd=0;

data comp;
    set paging end=eof;
    by param ;
    where page=&i;
    call symput('grp',compress(put(analgrln,best.)));
    /* Amend title as needed */
    _firtitl="Table 15.2.4.4.2 Analysis of Pharmacokinetic
Parameters of Nicotine Where >20% Missing Observations - PK Population";

    _upcas=(length(_firtitl)-
length(compress(_firtitl,'ABCDEFGHIJKLMNOPQRSTUVWXYZ')))/2;
    len=&blankn.-length("(Page &i of &tpage)");
    if eof then do;
        call symput('_FSRTITL', trim(left(_firtitl)));
        call symput('_blankn', compress(put(len,best.)));
        TITLE1="Table 15.2.4.4.2 Analysis of Pharmacokinetic
Parameters of Nicotine Where >20% Missing Observations";
        TITLE2="- PK Population";
        CALL SYMPUT('TITLE1', TRIM(LEFT(TITLE1)));
        CALL SYMPUT('TITLE2', TRIM(LEFT(TITLE2)));
    end;
    drop _firtitl _upcas len;
run;

ods listing close;

* most set up in template others below;
* title arial 12pt bold with 12pt paragraph space below;
* all headers to be arial 11pt bold;
* data arial 10pt;
* headers to be central, text values left aligned and numeric centered
around decimal point;
/* Update with your variables as needed */
proc report data = comp headline headskip missing nowd spanrows split =
'#'
%IF &I=1 %THEN %DO; CONTENTS=' ' %END; %ELSE %DO; CONTENTS='' %END;;
    column flag page param stat ("Group-&grp. PK &linebot." coll col2
col3) ;
    define flag / order noprint;
    define page / order order = internal noprint;

```

```

        define param          / group style={just=left cellwidth=2cm} "Variable"
;
        define stat           / display style={just=left cellwidth=2.5cm}
"Statistic";
        define col1           / display style={just=c/*d*/ cellwidth=2cm}
style(header)={just=center} "&&col1&grp";
        define col2           / display style={just=c/*d*/ cellwidth=2cm}
style(header)={just=center} "&&col2&grp";
        define col3           / display style={just=c/*d*/ cellwidth=2cm}
style(header)={just=center} "&&col3&grp";

        break after page / page;

break before flag / page %IF &I=1 %THEN %DO;
        CONTENTS="&_FSRTITL" %END; %ELSE %DO; CONTENTS='' %END;;

        compute before page / style={protectspecialchars=off};
        line "&linetop";
        endcomp;

        compute after page/style={just=center cellwidth=5cm
protectspecialchars=off};
        line "No analysis necessary";
        line " ";
        endcomp;

        compute before _page_ / style={just=left protectspecialchars=off};
        line "\b\fs24\sa24 &TITLE1."; /* \b = bold, \fs24 is font size
12pt, \sa24 is space after 12pt */;
        line "\b\fs24\sa24 &TITLE2."; /* \b = bold, \fs24 is font size
12pt, \sa24 is space after 12pt */;
        line "&linebot";
        endcomp;

        compute after param ;
        line " ";
        endcomp;

        compute after _page_ / style={just=left protectspecialchars=off
pretext="&linetop."};
        line "Note: &&foot&grp; THS = Tobacco Heating System.";
        line "";
        line "Appendix &ref.";
        line "Path: &TFLpath." &_blankn.*"\~\~" "(Page &i of
&tpage)";
        line "Program Run: &sysdate &sysuserid Program Status:
&status";
        endcomp;

run;
%end;
/*ods rtf close;*/
ods results on;
/*ods path sashelp.tmplmst (read);*/

```

```
ods path reset;
```

```
%mend ;
```

```
%outrtf(blankn=68, halfblnk=N, ref=15.4.4.4.2 and 15.3.3.1);
```

```
*=====;  
*  END OF PROGRAM CODE                               ;  
*=====;
```