

*****,

* Project : ZRHM-REXA-07-JP

*

* Program name : T1502042802_ZRHM-REXA-07_V1.sas

*

* Author : L. Yan

*

* Date created : 05/20/2015

*

* Purpose : Table T1502042802

*

* Revision History :

*

* Date Author Ref Revision (Date in YYYYMMDD format)

** 17Feb2016 M David Change from difference to geomean the original Wu code

*

*****,

%let table_n=T1502042802;

%let root=F:\PASS\ZRH\Unblinded Data - Team 2;

%let study=ZRHM-REXA-07-JP;

%let MPATH=ZRHM-REXA-07-JP\transfer-Wu\20150806 Wu\05Aug2015\macros;

%let SDTMP=&root.\&study.\data\sdtm;

%let ADAMP=&root.\&study.\data\adam;

```
%let opath=&root.\&study.\OUTPUT\AD HOC\RISK MARKERS\03 Final\OUTPUT;
```

```
%let lpath=&root.\&study.\OUTPUT\AD HOC\RISK MARKERS\03 Final\LOG;
```

```
%let odata=&root.\&study.\output\data;
```

```
%let csvdata=&root.\&study.\output\excel;
```

```
libname sdtm "&root.\&study\data\sdtm";
```

```
libname adam "&root.\&study\data\adam";
```

```
libname odata "&root.\&study\output\data";
```

```
*** pre-setting ***;
```

```
options missing=' ' nocenter ls=132 ps=45
```

```
formchar='|_---|+|---+=|-/<>*' charcode nodate nonumber;
```

```
run;
```

```
options nofmterr;
```

```
options papersize=letter orientation=landscape nodate nonumber center missing="" nobyline;
```

```
%global fdate;
```

```
options nofmterr;
```

```
data _null_;
```

```
    call symput("fdate",left(put("&sysdate"d, date9.)));
```

```
run;
```

```
%include "F:\PASS\ZRH\Unblinded Data - Team 2\POOLING\titlecsv.sas";
```

```
proc printto log="&lpath.\&table_n._ZRHM_REXA_07_JP_V4.lst" NEW;
```

```
run;
```

```
options sasautos=("F:\PASS\ZRH\Unblinded Data - Team 2\ZRHM-REXA-07-JP\transfer-Wu\20150806  
Wu\05Aug2015\macros" sasautos) notes;*/
```

```
*%init(delivery=1);
```

```
*%init(delivery=9);
```

```
%let prgname=&table_n._ZRHM_REXA_07_JP_V1;
```

```
options mprint;
```

```
%titlecsv(prgname=&prgname., version=4);
```

```
%put &title1;
```

```
%put &title2;
```

```
%put &APPENDIX;
```

```
%put &endpoint;
```

```
%put &outname.;
```

```
options missing="";
```

```
%macro cal_summary_pvalue(where=, outnum=, var=, in=, pflg=, decimal=1);
```

```
proc sort data=&in. out=anadt_&outnum.;
```

```
by usubjid;
```

```
where &where. ;
```

```
run;
```

```
proc sort data=anadt_&outnum.;
```

```
by trtcd;
```

```
run;
```

```
proc means data = anadt_&outnum. noprint;
```

```
by trtcd;
```

```
var &var.;
```

```
output out=xlab_&outnum. n=n mean=mean median=med std=sd min=min max=max q1=q1 q3=q3  
lclm=lclm uclm=uclm;
```

```
run;
```

```
data xlab_&outnum.;
```

```
set xlab_&outnum.;
```

```

n1    = trim(left(compress(put(n, 8.))));

%if &decimal=2 %then %do;

if sd > . then mean1 = (trim(left(compress(put(mean, 8.%eval(&decimal+1))))))|'|
(''|trim(left(compress(put(ceil(sd*1000)/1000, 8.%eval(&decimal+2))))))|'|');

else mean1 = (trim(left(compress(put(mean, 8.%eval(&decimal+1))))))|'| (NA)';

ci1=trim(left(compress(put(floor(lclm*1000)/1000, 8.%eval(&decimal+1)))))|'|',
'|'|trim(left(compress(put(ceil(uclm*1000)/1000, 8.%eval(&decimal+1))))));

%end;

%if &decimal=1 %then %do;

if sd > . then mean1 = (trim(left(compress(put(mean, 8.%eval(&decimal+1))))))|'|
(''|trim(left(compress(put(ceil(sd*1000)/1000, 8.%eval(&decimal+2))))))|'|');

else mean1 = (trim(left(compress(put(mean, 8.%eval(&decimal+1))))))|'| (NA)';

ci1=trim(left(compress(put(floor(lclm*100)/100, 8.%eval(&decimal+1)))))|'|',
'|'|trim(left(compress(put(ceil(uclm*100)/100, 8.%eval(&decimal+1))))));

%end;

%if &decimal=0 %then %do;

if sd > . then mean1 = (trim(left(compress(put(mean, 8.%eval(&decimal+1))))))|'|
(''|trim(left(compress(put(ceil(sd*100)/100, 8.%eval(&decimal+2))))))|'|');

else mean1 = (trim(left(compress(put(mean, 8.%eval(&decimal+1))))))|'| (NA)';

ci1=trim(left(compress(put(floor(lclm*10)/10, 8.%eval(&decimal+1)))))|'|',
'|'|trim(left(compress(put(ceil(uclm*10)/10, 8.%eval(&decimal+1))))));

%end;

median1 = trim(left(compress(put(med, 8.%eval(&decimal+1)))));

```

```

q1q3 = trim(left(compress(put(q1, 8.%eval(&decimal+1))))||', '||trim(left(compress(put(q3,
8.%eval(&decimal+1)))));

```

```

min1 = trim(left(compress(put(min, 8.%eval(&decimal+0))))||', '||trim(left(compress(put(max,
8.%eval(&decimal+0)))));

```

```

run;

```

```

proc means data = anadt_&outnum. noprint;

```

```

by trtcd;

```

```

var logaval;

```

```

output out=xlab1_&outnum. n=n mean=mean lclm=lclm uclm=uclm std=std;

```

```

run;

```

```

data xlab1_&outnum. ;

```

```

set xlab1_&outnum. ;

```

```

Estimate1 = exp(mean); /* Ratio of geometric mean */

```

```

LowerCL = exp(lclm); /* 95% CI lower bound */

```

```

UpperCL = exp(uclm); /* 95% CI upper bound */

```

```

CVperc=100*sqrt(exp(std**2)-1);

```

```

run;

```

```

data xlab1_&outnum.;

```

```

length geomean geoci $100;

```

```

set xlab1_&outnum.;

```

```

%if &decimal=2 %then %do;

```

```

if CVperc > . then geomean = (trim(left(compress(put(Estimate1, 8.%eval(&decimal+1))))||'
('||trim(left(compress(put(ceil(CVperc*1000)/1000, 8.2))))||')');

```

```

else geomean = (trim(left(compress(put(Estimate1, 8.%eval(&decimal+1))))))||' (NA)';

geoci=trim(left(compress(put(floor(lowercl*1000)/1000, 8.%eval(&decimal+1))))||',
'|trim(left(compress(put(ceil(uppercl*1000)/1000, 8.%eval(&decimal+1)))));

%end;

%if &decimal=1 %then %do;

if CVperc > . then geomean = (trim(left(compress(put(Estimate1, 8.%eval(&decimal+1))))))||'
('||trim(left(compress(put(ceil(CVperc*1000)/1000, 8.2))))||');

else geomean = (trim(left(compress(put(Estimate1, 8.%eval(&decimal+1))))))||' (NA)';

geoci=trim(left(compress(put(floor(lowercl*100)/100, 8.%eval(&decimal+1))))||',
'|trim(left(compress(put(ceil(uppercl*100)/100, 8.%eval(&decimal+1)))));

%end;

%if &decimal=0 %then %do;

if CVperc > . then geomean = (trim(left(compress(put(Estimate1, 8.%eval(&decimal+1))))))||'
('||trim(left(compress(put(ceil(CVperc*100)/100, 8.2))))||');

else geomean = (trim(left(compress(put(Estimate1, 8.%eval(&decimal+1))))))||' (NA)';

geoci=trim(left(compress(put(floor(lowercl*10)/10, 8.%eval(&decimal+1))))||',
'|trim(left(compress(put(ceil(uppercl*10)/10, 8.%eval(&decimal+1)))));

%end;

keep trtcd geomean geoci;

run;

```

```
proc sort data=xlabs1_outnum.;
```

```
by trtcd;
```

```
run;
```

```
proc sort data=xlabs_outnum.;
```

```
by trtcd;
```

```
run;
```

```
data xlabs_outnum.;
```

```
merge xlabs_outnum.(in=a) xlabs1_outnum.;
```

```
by trtcd;
```

```
run;
```

```
proc transpose data = xlabs_outnum. out=xlabs1_outnum. prefix=_;
```

```
id trtcd;
```

```
var n1 geomean geoci MEDIAN1 Q1Q3 MIN1 MEAN1 ci1; /** MD 17Feb2016***/
```

```
run;
```

```
data temp;
```

```
length _name_ _1 _2 _3 ord1 $100;
```

```
ord1="&outnum";
```

```
ordnum=input(ord1, best.);
```

```
_name_="";
```

```
_1="";
```

```
_2="";
```



```

_3="";

output;

run;

data rep_&outnum.;

length _name_ _1 _2 _3 ord1 $100;

set temp xlab_1_&outnum.;

ord1="&outnum";

ordnum=input(ord1, best.);

if upcase(_name_)="N1" then do; _name_="n"; sord=0; end;

if upcase(_name_)="GEOMEAN" then do; _name_="Geometric Mean (CV%)"; sord=1; end; /* MD
17Feb2016 */

if upcase(_name_)="GEOCI" then do; _name_="95% CI of Geometric Mean"; sord=2; end;

if upcase(_name_)="MEAN1" then do; _name_="Mean (SD)"; sord=8; end;

if upcase(_name_)="CI1" then do; _name_="95% CI"; sord=9; end;

if upcase(_name_)="MEDIAN1" then do; _name_="Median"; sord=5; end;

if upcase(_name_)="Q1Q3" then do; _name_="Q25, Q75"; sord=6; end;

if upcase(_name_)="MIN1" then do; _name_="Min, Max"; sord=7; end;

run;

data rep;

set rep rep_&outnum.;

run;

%mend;

```

```
%macro cal_sumary_pvalue1(where=, outnum=, var=, in=, pflg=, decimal=1);
```

```
proc sort data=&in. out=anadt_&outnum.;
```

```
by usubjid;
```

```
where &where. ;
```

```
run;
```

```
proc sort data=anadt_&outnum.;
```

```
by trtcd;
```

```
run;
```

```
proc means data = anadt_&outnum. noprint;
```

```
by trtcd;
```

```
var &var.;
```

```
output out=xlab_&outnum. n=n mean=mean median=med std=sd min=min max=max q1=q1 q3=q3  
lclm=lclm uclm=uclm;
```

```
run;
```

```
data xlab_&outnum.;
```

```
set xlab_&outnum.;
```

```
n1 = trim(left(compress(put(n, 8.))));
```

```
%if &decimal=2 %then %do;
```

```
if sd > . then mean1 = (trim(left(compress(put(mean, 8.%eval(&decimal+1)))))) || '  
( ' || trim(left(compress(put(ceil(sd*1000)/1000, 8.%eval(&decimal+2)))))) || ' )';
```

```

else mean1 = (trim(left(compress(put(mean, 8.%eval(&decimal+1)))))) || ' (NA)';

ci1=trim(left(compress(put(floor(lclm*1000)/1000, 8.%eval(&decimal+1)))) || ',
'| trim(left(compress(put(ceil(uclm*1000)/1000, 8.%eval(&decimal+1)))));

%end;

%if &decimal=1 %then %do;

if sd > . then mean1 = (trim(left(compress(put(mean, 8.%eval(&decimal+1)))))) || '
(' | trim(left(compress(put(ceil(sd*1000)/1000, 8.%eval(&decimal+2)))) || ')';

else mean1 = (trim(left(compress(put(mean, 8.%eval(&decimal+1)))))) || ' (NA)';

ci1=trim(left(compress(put(floor(lclm*100)/100, 8.%eval(&decimal+1)))) || ',
'| trim(left(compress(put(ceil(uclm*100)/100, 8.%eval(&decimal+1)))));

%end;

%if &decimal=0 %then %do;

if sd > . then mean1 = (trim(left(compress(put(mean, 8.%eval(&decimal+1)))))) || '
(' | trim(left(compress(put(ceil(sd*100)/100, 8.%eval(&decimal+2)))) || ')';

else mean1 = (trim(left(compress(put(mean, 8.%eval(&decimal+1)))))) || ' (NA)';

ci1=trim(left(compress(put(floor(lclm*10)/10, 8.%eval(&decimal+1)))) || ',
'| trim(left(compress(put(ceil(uclm*10)/10, 8.%eval(&decimal+1)))));

%end;

median1 = trim(left(compress(put(med, 8.%eval(&decimal+1)))));

q1q3 = trim(left(compress(put(q1, 8.%eval(&decimal+1)))) || ', ' | trim(left(compress(put(q3,
8.%eval(&decimal+1)))));

min1 = trim(left(compress(put(min, 8.%eval(&decimal+0)))) || ', ' | trim(left(compress(put(max,
8.%eval(&decimal+0)))));

run;

```

```
proc transpose data = xlab_&outnum. out=xlab_1_&outnum. prefix=_; /** Added prefix_ MD  
17Feb2016 ***/
```

```
id trtcd;
```

```
var n1 MEDIAN1 Q1Q3 MIN1 MEAN1 ci1;
```

```
run;
```

```
data temp;
```

```
length _name_ _1 _2 _3 ord1 $100;
```

```
ord1="&outnum";
```

```
ordnum=input(ord1, best.);
```

```
_name_="";
```

```
_1="";
```

```
_2="";
```

```
_3="";
```

```
output;
```

```
run;
```

```
data rep_&outnum.;
```

```
length _name_ _1 _2 ord1 $100;
```

```
set temp xlab_1_&outnum.;
```

```
ord1="&outnum";
```

```
ordnum=input(ord1, best.);
```

```
if upcase(_name_)="N1" then do; _name_="n"; sord=0; end;
```

```
if upcase(_name_)="GEOMEAN" then do; _name_="Geometric Mean (CV%)"; sord=1; end;
```

```
if upcase(_name_)="GEOCI" then do; _name_="95% CI of Geometric Mean"; sord=2; end;
```

```
if upcase(_name_)="MEAN1" then do; _name_="Mean (SD)"; sord=8; end;
```

```
if upcase(_name_)="CI1" then do; _name_="95% CI"; sord=9; end;
```

```
if upcase(_name_)="MEDIAN1" then do; _name_="Median"; sord=5; end;  
if upcase(_name_)="Q1Q3" then do; _name_="Q25, Q75"; sord=6; end;  
if upcase(_name_)="MIN1" then do; _name_="Min, Max"; sord=7; end;  
run;
```

```
data rep;  
  
set rep rep_&outnum.;  
  
run;
```

```
%mend;
```

```
proc sort data=adam.adsl out=trt;  
  
by usubjid;  
  
where FASFL="Y";  
  
run;
```

```
data trt;  
  
set trt;  
  
if TRT01A="THSm2.2" then trtcd=1;  
  
else if TRT01A="mCC" then trtcd=2;  
  
else if TRT01A="SA" then trtcd=3;  
  
run;
```

```
proc sort data=adam.adlb out=anald;
```

```
by usubjid;  
  
where paramcd in ("FIBRINO") and avisitn>=100 and FASFL="Y" and anl01fl="Y";  
  
run;
```

```
data anald;  
  
set anald;  
  
if aval>. then logaval=log(aval);  
  
run;
```

```
proc sort data=anald out=check(keep=paramn avisitn avisit) nodupkey;  
  
by paramn avisitn avisit;  
  
run;
```

```
data trt_1;  
  
set trt;  
  
run;
```

```
data anald;  
  
set anald;  
  
if TRTA="THSm2.2" then trtcd=1;  
  
else if TRTA="mCC" then trtcd=2;  
  
else if TRTA="SA" then trtcd=3;  
  
if aval>0 then logaval=log(aval);  
  
run;
```

```
data check;
```

```
set check;
```

```
ord=_n_;
```

```
run;
```

```
%*cal_summary_pvalue(where=1, outnum=1, var=aval, in=anald, pflg=1);
```

```
data rep;
```

```
run;
```

```
data _null_;
```

```
set check;
```

```
call execute ('%cal_summary_pvalue(where=%str(avisitn='||avisitn||' and paramn='||paramn||'),  
outnum='||ord||', var=aval, in=anald);');
```

```
run;
```

```
data rep1;
```

```
set rep;
```

```
run;
```

```
data rep;
```

```
run;
```

```
data _null_;
```

```
set check;
```

```
if avisitn>100;  
  
    call execute ('%cal_summary_pvalue1(where=%str(avisitn='||avisitn||' and paramn='||paramn||'),  
outnum='||ord||', var=PCHG, in=anald);');  
  
run;
```

```
data rep2;  
  
set rep;  
  
rename _1=_4 _2=_5 _3=_6;  
  
run;
```

```
data frep;  
  
merge rep1 rep2;  
  
by ordnum sord;  
  
run;
```

```
data frep;  
  
set frep;  
  
ord=ORDNUM;  
  
run;
```

```
data frep;  
  
merge frep(in=a) check;  
  
by ord;  
  
if a;  
  
if avisitn>.;  
  
run;
```



```
proc sort data=trt_1 nodupkey;  
  
by trtcd usubjid;  
  
run;
```

```
proc freq data = trt_1 noprint;  
  
tables trtcd/ out= denom;  
  
run;
```

```
data _null_;  
  
set denom end=eof;
```

```
retain total 0;
```

```
total = total+count;
```

```
if trtcd= 1 then do;  
  
call symput('trt1', trim(left(put(count,8)))));  
  
end;
```

```
if trtcd= 2 then do;  
  
call symput('trt2', trim(left(put(count,8)))));  
  
end;
```

```
if trtcd= 3 then do;
```

```
call symput('trt3', trim(left(put(count,8))));
```

```
end;
```

```
run;
```

```
%put trt1=&trt1 trt2=&trt2 trt3=&trt3;
```

```
data smalln;
```

```
set frep;
```

```
if _name_="n";
```

```
run;
```

```
data smalln;
```

```
set smalln;
```

```
_name_="Missing, n(%)";
```

```
sord=0.1;
```

```
if _1 ne "" then _1=strip(put((&trt1-input(_1, best.)), 8.0))||" ("||strip(put((&trt1-input(_1, best.))*100/&trt1, 8.1))||")";
```

```
if _2 ne "" then _2=strip(put((&trt2-input(_2, best.)), 8.0))||" ("||strip(put((&trt2-input(_2, best.))*100/&trt2, 8.1))||")";
```

```
if _3 ne "" then _3=strip(put((&trt3-input(_3, best.)), 8.0))||" ("||strip(put((&trt3-input(_3, best.))*100/&trt3, 8.1))||")";
```

```
if _4 ne "" then _4=strip(put((&trt1-input(_4, best.)), 8.0))||" ("||strip(put((&trt1-input(_4, best.))*100/&trt1, 8.1))||")";
```

```
if _5 ne "" then _5=strip(put((&trt2-input(_5, best.)), 8.0))||" ("||strip(put((&trt2-input(_5, best.))*100/&trt2, 8.1))||")";
```

```
if _6 ne "" then _6=strip(put((&trt3-input(_6, best.)), 8.0))||" ("||strip(put((&trt3-input(_6, best.))*100/&trt3, 8.1))||")";
```

```
run;
```

```
/*
```

```
data frep;
```

```
set frep smalln;
```

```
run;
```

```
*/
```

```
data frep;
```

```
set frep;
```

```
if _1 in ("0 (0.0)" " ") and _2 in ("0 (0.0)" " ") and _4 in ("0 (0.0)" " ") and _5 in ("0 (0.0)" " ") and _3 in ("0 (0.0)" " ") and _6 in ("0 (0.0)" " ") then delete;
```

```
run;
```

```
data frep;
```

```
set frep;
```

```
if _1="0 (0.0)" then _1="0";
```

```
if _2="0 (0.0)" then _2="0";
```

```
if _3="0 (0.0)" then _3="0";
```

```
if _4="0 (0.0)" then _4="0";
```

```
if _5="0 (0.0)" then _5="0";
```

```
if _6="0 (0.0)" then _6="0";
```

```
run;
```

```
proc sort data=frep;  
by paramn avisitn avisit sord;  
run;
```

```
proc sort data=anald out=fmt(keep=paramn param) nodupkey;  
by paramn param;  
run;
```

```
data fmt;  
set fmt;  
fmtname="grp";  
start=paramn;  
label="Parameter: "||strip(param);  
run;
```

```
proc format cntlin=fmt;  
run;
```

```
%macro cal_part_main();
```

```
data frep;  
set frep;  
avisit=propcase(avisit);
```

```
if AVISIT="Day 0" then avisit="Baseline";
```

```
%do i = 1 %to 100;
```

```
if (&i-1)*1<ordnum<=&i*1 then pagen=&i;
```

```
%end;
```

```
run;
```

```
%mend;
```

```
%cal_part_main();
```

```
data frep;
```

```
set frep;
```

```
space="";
```

```
run;
```

```
data odata.&prgname.;
```

```
set frep;
```

```
run;
```

```
%global totalpage1;
```

```
data _null_;
```

```
set frep end=eof;
```

```
if eof then do;
```

```
    call symput('totalpage1', trim(left(put(pagen,8))));
```

```
end;
```

```
run;
```

```
%put totalpage1=&totalpage1;
```

```
/*title(prgname1=&prgname.);
```

```
%let fprgname=&table_n._ZRHM_REXA_07_JP_V4; /* MD 17FEB2016 */
```

```
%let repversion=Final v4.0; /* - Draft v0.1 - MD 17FEB2016 */
```

```
%let outname=%lowercase(&table_n.)-ZRHM-REXA-07-JP-fibr-v4; /* MD 17FEB2016 */
```

```
%trtrtfg(pgmname=&outname., pgmid=1, new=0, style=, bookmark=%lowercase(&outname.));
```

```
%macro reppart;
```

```
%do i = 1 %to &totalpage1;
```

```
proc report data=frep headskip headline spacing=4 nowd split='~' style=[outputwidth=100%]  
style(header column)=[protectspecialchars=off];
```

```
where pagen=&i.;
```

```
column pagen paramn avisitn avisit sord _name_ ("\\brdrb\\brdrs THSm2.2 (N=&trt1.)" _1 _4) space  
("\\brdrb\\brdrs mCC (N=&trt2.)" _2 _5) space ("\\brdrb\\brdrs SA (N=&trt3.)" _3 _6);
```

```
define pagen /order order=internal noprint;
```

```
define paramn /order order=internal noprint;
```

```
define avisitn /order order=internal noprint;
```

```
define avisit /order "Time point" flow style(column)=[cellwidth=10% just=l];
```

```
define sord /order order=internal noprint;
```

```
define _name_ /display "Statistic" flow style(column)=[cellwidth=15% just=l];
```

```
define _1 /display "Raw value" flow style(column)=[cellwidth=10% just=c];
```

```
define _4 /display "% Change(*)" flow style(column)=[cellwidth=10% just=c];
```

```
define space /display " " flow style(column)=[cellwidth=0.5% just=c];
```

```
define _2 /display "Raw value" flow style(column)=[cellwidth=10% just=c];
```

```
define _5 /display "% Change(*)" flow style(column)=[cellwidth=10% just=c];
```

```
define space /display " " flow style(column)=[cellwidth=0.5% just=c];
```

```
define _3 /display "Raw value" flow style(column)=[cellwidth=10% just=c];
```

```
define _6 /display "% Change(*)" flow style(column)=[cellwidth=10% just=c];
```

COMPUTE after avisitn ;

LINE @1 "";

ENDCOMP;

compute before pagen;

line @1 "";

endcomp;

compute before _page_ /style=[fontweight=bold fontsize=3.75];

line @1 "&title1 &title2";

line @1 " ";

LINE @1 paramn grp.;

line @1 "^R/RTF\brdrb\brdrs\brdrw30\brsp20\b ' ";

endcomp;

compute after _page_ /style=[fontsize=1.75];

line @1 "Note: mCC = Menthol conventional cigarettes; SA = Smoking abstinence; THSm2.2 = Tobacco Heating System 2.2 Menthol.";

line @1 "Note: Percentages are based on the number of subjects indicated in the column header (N).";

line @1 "Note: * % change from baseline, where baseline is defined as the last assessment prior to first randomized product use in mCC / THS 2.2 Menthol";

line @1 "arms or the last assessment prior to 10 AM on Day 1 in the SA arm";

line @1 " ";

line @1 "&APPENDIX.";

line @1 "Study ID:ZRHM-REXA-07-JP Program: &fprgname..sas Status: &repversion./&fdate.
Page: &i. of &totalpage1";

endcomp;

run;

%end;

%mend;

%reppart;

ods listing;

ods rtf close;

proc printto;

run;