

```

*****;
* Project          : ZRHM-REXA-07-JP
*
* Program name     : t1502043701_ZRHM_REXA_07_amceq.sas
*
* Author          : L. Yan
*
* Date created     : 05/20/2015
*
* Purpose         : Table t1502043701
* Revision History :
*
* Date      Author      Ref      Revision (Date in YYYYMMDD format)
*
*****;

%let prgname=T1502043701_ZRHM_REXA_07_JP_V1;

options mprint;

options sasautos=("W:\pmp07\macros" sasautos) notes;
%init(delivery=9);

%titlecsv(prgname=&prgname., version=3);

%put &title1;
%put &title2;
%put &APPENDIX;
%put &endpoint;
%put &outname.;
%global decimal;
%let decimal=0;

%macro cal_sumary_pvalue(wher=, outnum=, var=, in=, pflg=, decimal=0);

proc sort data=&in. out=anadt_&outnum.;
by usbjid;
where &wher. ;
run;

proc sort data=anadt_&outnum.;
by trtcd;
run;

proc means data = anadt_&outnum. noprint;
by trtcd;
var &var.;
output out=xlab_&outnum. n=n mean=mean median=med std=sd min=min max=max q1=q1 q3=q3 lclm=lclm uclm=uclm;
run;

data xlab_&outnum.;
set xlab_&outnum.;
n1      = trim(left(compress(put(n, 8.))));

%if &decimal=1 %then %do;
if sd > . then mean1 = (trim(left(compress(put(mean, 8.%eval(&decimal+1))))))||' ('||trim(left(compress(put(ceil(sd*1000)/1000, 8.%eval(&decimal+2))))))||')';
else mean1 = (trim(left(compress(put(mean, 8.%eval(&decimal+1))))))||' (NA)';
ci1=trim(left(compress(put(floor(lclm*100)/100, 8.%eval(&decimal+1))))||', '||trim(left(compress(put(ceil(uclm*100)/100, 8.%eval(&decimal+1))))));
%end;
%if &decimal=0 %then %do;
if sd > . then mean1 = (trim(left(compress(put(mean, 8.%eval(&decimal+1))))))||' ('||trim(left(compress(put(ceil(sd*100)/100, 8.%eval(&decimal+2))))))||')';
else mean1 = (trim(left(compress(put(mean, 8.%eval(&decimal+1))))))||' (NA)';
ci1=trim(left(compress(put(floor(lclm*10)/10, 8.%eval(&decimal+1))))||', '||trim(left(compress(put(ceil(uclm*10)/10, 8.%eval(&decimal+1))))));
%end;

median1 = trim(left(compress(put(med, 8.%eval(&decimal+1)))));
q1q3    = trim(left(compress(put(q1, 8.%eval(&decimal+1))))||', '||trim(left(compress(put(q3, 8.%eval(&decimal+1))))));
;
min1    = trim(left(compress(put(min, 8.%eval(&decimal+0))))||', '||trim(left(compress(put(max, 8.%eval(&decimal+0))))));
run;

proc transpose data = xlab_&outnum. out=xlab_1_&outnum.;
id trtcd;
var n1 mean1 ci1 median1 q1q3 min1;
run;

data rep_&outnum.;
length _name_ _1 _2 /*_3*/ ord1 $100;

```

```

set xlab_1_&outnum.;
ord1="&outnum";
ordnum=input(ord1, best.);
if upcase(_name_)="N1" then do; _name_="n"; sord=0; end;

if upcase(_name_)="MEAN1" then do; _name_="Mean (SD)"; sord=5; end;
if upcase(_name_)="CI1" then do; _name_="95% CI of Mean"; sord=6; end;
if upcase(_name_)="MEDIAN1" then do; _name_="Median"; sord=2; end;
if upcase(_name_)="Q1Q3" then do; _name_="Q25, Q75"; sord=3; end;
if upcase(_name_)="MIN1" then do; _name_="Min, Max"; sord=4; end;
run;

data rep;
set rep rep_&outnum.;
run;

%mend;
%macro mainloop(flg=, outn=, where=);

proc sort data=adam.adsl out=trt;
by usubjid;
where &flg.="Y";
run;

data trt;
set trt;
if TRT01P="THSm2.2" then trtcd=1;
else if TRT01P="mCC" then trtcd=2;
else if TRT01P="SA" then trtcd=3;
run;

proc sort data=adam.adqspa out=advs;
by usubjid;
where paramn in (18 19 20 21 22) and &flg.="Y" and &where.;
run;

data advs;
set advs;
decimal=compress(scan(avalc, 2, "."));
if decimal ne "" then decin=length(decimal);
else decin=0;
run;

proc sort data=advs out=check1;
by paramn decin;
run;

data check1;
set check1;
by paramn decin;
if last.paramn;
keep paramn decin;
run;

proc sort data=advs out=check(keep=paramn avisitn avisit param paramcd) nodupkey;
by paramn avisitn avisit;
run;

data check;
merge check(in=a) check1;
by paramn;
if a;
run;

data trt_1;
set trt;
run;

data advs;
set advs;
if TRTP="THSm2.2" then trtcd=1;
else if TRTP="mCC" then trtcd=2;
else if TRTP="SA" then trtcd=3;
run;

data check;
set check;
ord=_n_;
run;

%*cal_summary_pvalue(where=1, outnum=1, var=aval, in=advs, pflg=1);

data rep;
run;

data _null_;

```

```

    set check;
    call execute ('%cal_summary_pvalue(where=%str(avisitn='||avisitn||' and paramn='||paramn||' ), outnum='||ord||', var
=aval, in=adv, decimal='||decin||' );');
run;

data rep1;
set rep;
run;

data rep;
run;

data _null_;
set check;
if avisitn>100;
call execute ('%cal_summary_pvalue(where=%str(avisitn='||avisitn||' and paramn='||paramn||' ), outnum='||ord||', var
=PCHG, in=adv, decimal=1);');
run;

data rep2;
set rep;
rename _1=_4 _2=_5 /*_3=_6*/;
run;

proc sort data=rep1;
by ordnum sord;
run;

proc sort data=rep2;
by ordnum sord;
run;

data frep;
merge rep1 rep2;
by ordnum sord;
run;

data frep;
set frep;
ord=ORDNUM;
run;

data frep;
set frep;

%do i = 1 %to 100;
if (&i-1)*2<ordnum<=&i*2 then pagen=&i;
%end;

run;

data frep;
set frep;
space="";
run;

data frep&outn.;
merge frep(in=a) check;
by ord;
if a;
if avisit="Day 0" then avisit="Baseline";
if avisitn>.;
run;

proc sort data=trt_1 nodupkey;
by trtcd usubjid;
run;

proc freq data = trt_1 noprint;
tables trtcd/ out= denom;
run;

%global trt1_&outn. trt2_&outn. trt3_&outn.;
data _null_;
set denom end=eof;

retain total 0;

total = total+count;

if trtcd= 1 then do;
call symput("trt1_&outn.", trim(left(put(count,8)))));
end;
if trtcd= 2 then do;
call symput("trt2_&outn.", trim(left(put(count,8)))));

```

```

end;
if trtcd= 3 then do;
  call symput("trt3_&outn.", trim(left(put(count,8)))));
end;

run;

data smalln&outn.;
set frep&outn.;
if _name_="n";
run;

data smalln&outn.;
set smalln&outn.;
_name_="Missing, n(%)";
sord=0.1;
if _1 ne "" then _1=strip(put((&trt1_&outn.-input(_1, best.)), 8.0))||" ("||strip(put((&trt1_&outn.-input(_1, best.))*
100/&&trt1_&outn., 8.1))||")";
if _2 ne "" then _2=strip(put((&trt2_&outn.-input(_2, best.)), 8.0))||" ("||strip(put((&trt2_&outn.-input(_2, best.))*
100/&&trt2_&outn., 8.1))||")";
if _4 ne "" then _4=strip(put((&trt1_&outn.-input(_4, best.)), 8.0))||" ("||strip(put((&trt1_&outn.-input(_4, best.))*
100/&&trt1_&outn., 8.1))||")";
if _5 ne "" then _5=strip(put((&trt2_&outn.-input(_5, best.)), 8.0))||" ("||strip(put((&trt2_&outn.-input(_5, best.))*
100/&&trt2_&outn., 8.1))||")";
run;

data frep&outn.;
set frep&outn. smalln&outn.;
run;

data frep&outn.;
set frep&outn.;
if _1 in ("0 (0.0)" " ") and _2 in ("0 (0.0)" " ") and _4 in ("0 (0.0)" " ") and _5 in ("0 (0.0)" " ") then delete;
run;

data frep&outn.;
set frep&outn.;
if _1 in ("0 (0.0)") then _1="0";
if _2 in ("0 (0.0)") then _2="0";
if _4 in ("0 (0.0)") then _4="0";
if _5 in ("0 (0.0)") then _5="0";
run;

proc sort data=frep&outn.;
by pagen paramn avisitn avisit sord;
run;

%mend;

%mainloop(flag=PPROT1FL, outn=1, where=%str(100<=avisitn<=106 and anl01fl="Y"));
%mainloop(flag=PPROT2FL, outn=2, where=%str(avisitn in (100, 130) and anl01fl="Y"));
%mainloop(flag=PPROT3FL, outn=3, where=%str(avisitn in (100, 160) and anl01fl="Y"));
%mainloop(flag=PPROT4FL, outn=4, where=%str(avisitn in (100, 190) and anl01fl="Y"));

proc sort data=advs out=fmt(keep=paramn param) nodupkey;
by paramn param;
run;

data fmt;
set fmt;
fmtname="grp";
start=paramn;
label="Parameter: "||strip(param);
run;

proc format cntlin=fmt;
run;

data odata.&prgname.;
set frep1 (in=a) frep2 (in=b) frep3 (in=c) frep4 (in=d);
if a then group="PPROT1FL";
if b then group="PPROT2FL";
if c then group="PPROT3FL";
if d then group="PPROT4FL";
run;

%global totalpage1;

data _null_;
set frep1 end=eof;

if eof then do;

```

```

        call symput('totalpage1', trim(left(put(pagen,8)))));
    end;

run;

%put totalpage=&totalpage1;

data frep2;
set frep2;
pagen=pagen+&totalpage1;
run;

%global totalpage2;

data _null_;
    set frep2 end=eof;

    if eof then do;
        call symput('totalpage2', trim(left(put(pagen,8)))));
    end;

run;

%put totalpage=&totalpage2;

data frep3;
set frep3;
pagen=pagen+&totalpage2;
run;

%global totalpage3;

data _null_;
    set frep3 end=eof;

    if eof then do;
        call symput('totalpage3', trim(left(put(pagen,8)))));
    end;

run;

%put totalpage=&totalpage3;

data frep4;
set frep4;
pagen=pagen+&totalpage3;
run;

%global totalpage4;

data _null_;
    set frep4 end=eof;

    if eof then do;
        call symput('totalpage4', trim(left(put(pagen,8)))));
    end;

run;

data allrep;
set frep1 (in=a) frep2 (in=b) frep3 (in=c) frep4 (in=d);
if a then group=1;
if b then group=2;
if c then group=3;
if d then group=4;
drop pagen;
run;

proc sort data=allrep;
by paramn group avisitn;
run;

proc sort data=allrep out=page(keep=paramn group avisitn) nodupkey;
by paramn group avisitn;
run;

data page;
set page;

```

```

pagen=_n_;
run;

data allrep;
merge allrep page;
by paramn group avisitn;
run;

%global totalpage4;

data _null_;
set allrep end=eof;

if eof then do;
call symput('totalpage4', trim(left(put(pagen,8)))));
end;

run;

%trtrtfg(pgmname=&outname., pgmid=1, new=0, style=, bookmark=%lowcase(&outname.));

%macro reppart (where=, group=, pagen=);

proc report data=allrep headskip headline spacing=4 nowd split='~' style=[outputwidth=100%] style(header column)=[protectspecialchars=off];
where &where.;
column pagen paramn avisitn avisit sord _name_ ("~\brdrb\brdrs THSm2.2 (N=&&trt1_&group.)" _1 _4) space ("~\brdrb\brdrs mCC (N=&&trt2_&group.)" _2 _5);
define pagen /order order=internal noprint;
define paramn /order order=internal noprint;
define avisitn /order order=internal noprint;
define avisit /order "Time point" flow style(column)=[cellwidth=10% just=l];
define sord /order order=internal noprint;

define _name_ /display "Statistic" flow style(column)=[cellwidth=10% just=l];
define _1 /display "Raw value" flow style(column)=[cellwidth=10% just=c];
define _4 /display "% Change(*)" flow style(column)=[cellwidth=10% just=c];
define space /display " " flow style(column)=[cellwidth=0.5% just=c];

define _2 /display "Raw value" flow style(column)=[cellwidth=10% just=c];
define _5 /display "% Change(*)" flow style(column)=[cellwidth=10% just=c];

COMPUTE after avisitn ;
LINE @1 "";
ENDCOMP;

break after pagen/page;

compute before pagen;
line @1 "";
endcomp;

compute before _page_ /style=[fontweight=bold fontsize=3.75];
line @1 "&title1 &title2";
line @1 " ";
LINE @1 paramn grp.;
line @1 "Product Use Time Period: Period &group.";
line @1 "~^R/RTF'\brdrb\brdrs\brdrw30\brsp20\b ' ' ";
endcomp;

compute after _page_/style=[fontsize=1.75];
line @1 "Note: mCC = Menthol conventional cigarettes; THSm2.2 = Tobacco Heating System 2.2 Menthol .";
line @1 "Note: Percentages are based on the number of subjects indicated in the column header (N).";
line @1 "Note: * % change from baseline, where baseline is defined as the last assessment prior to first randomized product use in mCC / THS 2.2 Menthol arms.";
line @1 "Note: Periods defined as Period 1 ([Day 1 ~ Day 6 confinement]), Period 2 ([Day 6 ambulatory ~ Day 30 Visit]), Period 3 ([Day 30 Visit ~ Day 60 Visit]);
line @1 "and Period 4 ([Day 60 Visit ~ Day 90 Visit]). ";
line @1 " ";
line @1 "&APPENDIX.";
line @1 "Study ID:ZRHM-REXA-07-JP Program: &fprgname..sas Status: &repversion./&fdate. Page: &pagen. of &totalpage4";
endcomp;
run;

%mend;

proc sort data=page;
by pagen;
run;

data _null_;
set page;

```

```
    by pagen;  
        call execute ('%reppart(where=%str(pagen='||pagen||'), group='||group||', pagen='||pagen||');');  
run;
```

```
ods listing;  
ods rtf close;
```