

```

/*=====
| Covance Study Number      : 000000106343
| Program Name              : t_mhbma_pp.sas
| Purpose                   : Program to create table 15.2.4.2.1
| Input Data                : ADAM.ADSL, ADAM.ADBX
| Output Data               : T_15_02_04_02_01
| Macros Called             : %m_printto, %param, %stats, %outtrtf, %m_logchk
|
| Originally Performed by   : Upender S
| Date                     : 28APR2015
|
|=====
| Modification History
|-----
| Modified by              :
| Modification Date        :
| Modification Description :
|=====*/

%m_printto(route=YES);

%let TFL_Part=%scan(&_SASPROGRAMFILE,-3,%str(/));

ods results on;
ods path sashelp.tmplmst (read);

data _null_;
    tmp="%TFL_Part";
    if tmp not in ("dev" "qc") then call symput("TFL_Part", "prod");
    call symput('TFLpath', compress("&_SASPROGRAMFILE",""));
    call symput('TFLprg',reverse(scan(strip(reverse(compress("&_SASPROGRAMFILE","")),1,"/"))));
run;

data adbx;
set adam.adbx (where=((pprot1f1 = "Y" or pprot2f1 = "Y" or pprot3f1 = "Y" or pprot4f1 = "Y") and an102f1='Y' ));
run;

data adbx1 (drop=trtpn rename=(trtpn_=trtpn));
set adbx;
if trtp='THSm2.2' then trtpn_=1;
if trtp='mCC' then trtpn_=2;
if trtp='SA' then trtpn_=trtpn;

if trtpn_=1 then cat='1';
if trtpn_=2 then cat='2';
if trtpn_=3 then cat='3';
run;

proc sql exec; select count(distinct usubjid) into: N1THS from adam.adsl(where=(trt01pn = 4 and pprot1f1 = "Y")); quit;
proc sql exec; select count(distinct usubjid) into: N1MCC from adam.adsl(where=(trt01pn = 5 and pprot1f1 = "Y"));quit;
proc sql exec; select count(distinct usubjid) into: N1SAA from adam.adsl(where=(trt01pn = 3 and pprot1f1 = "Y"));quit;
proc sql exec; select count(distinct usubjid) into: N2THS from adam.adsl(where=(trt01pn = 4 and pprot2f1 = "Y"));quit;
proc sql exec; select count(distinct usubjid) into: N2MCC from adam.adsl(where=(trt01pn = 5 and pprot2f1 = "Y"));quit;
proc sql exec; select count(distinct usubjid) into: N2SAA from adam.adsl(where=(trt01pn = 3 and pprot2f1 = "Y"));quit;
proc sql exec; select count(distinct usubjid) into: N3THS from adam.adsl(where=(trt01pn = 4 and pprot3f1 = "Y"));quit;
proc sql exec; select count(distinct usubjid) into: N3MCC from adam.adsl(where=(trt01pn = 5 and pprot3f1 = "Y"));quit;
proc sql exec; select count(distinct usubjid) into: N3SAA from adam.adsl(where=(trt01pn = 3 and pprot3f1 = "Y"));quit;
proc sql exec; select count(distinct usubjid) into: N4THS from adam.adsl(where=(trt01pn = 4 and pprot4f1 = "Y"));quit;
proc sql exec; select count(distinct usubjid) into: N4MCC from adam.adsl(where=(trt01pn = 5 and pprot4f1 = "Y"));quit;
proc sql exec; select count(distinct usubjid) into: N4SAA from adam.adsl(where=(trt01pn = 3 and pprot4f1 = "Y"));quit;

%macro param(paramcd=, x=);

    data &paramcd._orig;
    set adbx1;
    where paramcd = "&paramcd.";
    run;

%macro stats(colvar=);

data co_1;
    set &paramcd._orig;
    where (pprot1f1 = "Y" and 101<=avisitn <= 105) or (pprot2f1 = "Y" and avisitn = 130) or (pprot3f1 = "Y" and avisitn = 160) or (p
prot4f1 = "Y" and avisitn = 190);
    where also paramcd = "&paramcd." and avalc ne " " ;

```

```

    if avisit in ('DAY -1' 'DAY 0') then delete;

if not missing(&colvar.) and &colvar. > 0 then ageo=log(&colvar.);

    if not missing(&colvar.) then dataflg=1;
    keep usubjid paramn cat avisitn avisit &colvar. AQLFL ageo dataflg apuper apuperc;
run;

data baseline ;
set &paramcd._orig;;
    where paramcd = "&paramcd." ;

if &colvar. ^=. and &colvar. > 0 then ageo=log(&colvar.);
    if not missing(&colvar.) then dataflg=1;

    if ablf1='Y' and pprot1f1 = "Y" then do; avisit='Baseline'; avisitn=10; apuper = 1; apuperc = "Period 1"; output; end;
    if ablf1='Y' and pprot2f1 = "Y" then do; avisit='Baseline'; avisitn=10; apuper = 2; apuperc = "Period 2";output; end;
    if ablf1='Y' and pprot3f1 = "Y" then do; avisit='Baseline'; avisitn=10; apuper = 3; apuperc = "Period 3"; output; end;
    if ablf1='Y' and pprot4f1 = "Y" then do; avisit='Baseline'; avisitn=10; apuper = 4; apuperc = "Period 4";output; end;
    keep usubjid paramn cat avisitn avisit &colvar. AQLFL ageo apuper apuperc;
run;

proc sort data=baseline NODUPKEY;
by apuper apuperc usubjid cat avisit avisitn &colvar.;
run;

data co_1b;
set co_1 baseline;
run;

proc sort data=co_1b; by apuper apuperc avisitn avisit cat; run;

** BLQ Counts **;

proc sort data=co_1b out=co_1bq nodupkey dupout=blqdups; by usubjid paramn cat avisitn ; run;

proc sql;
    create table co_2t as select apuper, apuperc, cat, count(distinct usubjid) as tot from co_1bq group by apuper, apuperc, cat orde
r by apuper, apuperc,cat;
    create table co_2c as select apuper, apuperc,cat, avisitn, avisit, 'BLQ' as _stat_ length=8, sum(AQLFL='Y') as count from co_1bq

        group by apuper, apuperc,cat, avisitn, avisit order by apuper, apuperc, cat, avisitn;
    create table co_2s as select apuper, apuperc,cat, avisit, avisitn,count(distinct usubjid) as stot from co_1bq where dataflg=1
        group by apuper, apuperc, cat ,avisitn, avisit order by apuper, apuperc, cat, avisitn;
quit;

data co_2bX; /* 1) JH 23OCT2014 */
    merge co_2c(in=a) co_2t /*co_2s*/; /* 1) JH 23OCT2014 */
    by apuper apuperc cat;
    if a;
run;

/* 1) JH 23OCT2014 - START */
DATA CO_2B;
    MERGE CO_2BX(IN=A) CO_2S;
    BY apuper apuperc CAT AVISITN AVISIT;
    IF A;
RUN;
/* 1) JH 23OCT2014 - END */

proc sort data=co_1b ;
by apuper apuperc avisitn avisit cat &colvar.;
run;

** Normal Stats **;
proc means data=co_1b noprint;
/*where &colvar ne .;*/
    var &colvar.;
    by apuper apuperc avisitn avisit cat;
    output out=co_2s(drop=_freq_ _type_) n=n mean=mean std=std median=med min=min max=max p25=q25 p75=q75 lclm =c195 uclm=cu95;
run;

****combining BLQ stats with rest of the stats ****;
```

```

proc sort data=CO_2B ; by apuper apuperc avisitn avisit cat; run;

data co_2s_blq;
merge co_2s (in=a) CO_2B (in=b drop=_stat_ tot stot rename=(count=blq));
by apuper apuperc avisitn avisit cat;
run;

data co_2s_1;
set co_2s_blq;
if apuper = 1 then do;
period = "Period 1";
if cat= '1' then BigN= &N1THS;
if cat= '2' then BigN = &N1mcc;
if cat= '3' then BigN = &N1saa;
end;
else if apuper = 2 then do;
period = "Period 2";
if cat='1' then BigN= &n2ths;
if cat='2' then BigN = &n2mcc;
if cat='3' then BigN = &n2saa;
end;
else if apuper = 3 then do;
period = "Period 3";
if cat='1' then BigN= &N3THS;
if cat='2' then BigN = &N3mcc;
if cat='3' then BigN = &N3saa;
end;
else if apuper = 4 then do;
period = "Period 4";
if cat='1' then BigN= &N4THS;
if cat='2' then BigN = &N4mcc;
if cat='3' then BigN = &N4saa;
end;

end;

msng=BigN-n;
if .<msng^=0 then msng_prcnt=(msng/BigN)*100;
if .<blq^=0 then bloq_prcnt=(blq/N)*100;
run;

data co_2s_c;
length N mean_sd min_max median q25_q75 c195_cu95 msg_pct blq_pct $50.;
set co_2s_1(rename=(n=n_orig));

if c195 ne . then c195 = 0.01*floor(100*c195);
if cu95 ne . then cu95 = 0.01*ceil(100*cu95);

if n_orig ^=. then N = compress(put(n_orig,best.));
if .<msng^=0 then msg_pct=compress(put(msng, best.))||' ('||compress(put(msng_prcnt, 5.1))||')';
if .<blq^=0 then blq_pct=compress(put(blq, best.))||' ('||compress(put(bloq_prcnt, 5.1))||')';
if mean ^=. and std ^=. then mean_sd=strip(put(mean,12.2))||" ("||strip(put(std,12.3))||")";
if min ^=. and max ^=. then min_max = strip(put(min,12.1))||", "||strip(put(max,12.1));
if med ^=. then median = strip(put(med,12.2));
if q25^=. and q75^=. then q25_q75= strip(put(q25,12.2))||", "||strip(put(q75,12.2));
if c195^=. and cu95^=. then c195_cu95= strip(put(c195,12.2))||", "||strip(put(cu95,12.2));
run;

proc transpose data=co_2s_c out=co_2s_ct(rename=(name=_stat_ col1=&colvar.));
by apuper apuperc avisitn avisit cat;
var N msg_pct blq_pct mean_sd median min_max q25_q75 c195_cu95;
run;

data co_2s_ct (rename=(stat=_stat_));
length stat $10.;
set co_2s_ct;
stat=_stat_;
drop _stat_;
run;

** Geometric Stas **;
proc means data=co_1b noprint mean std lclm uclm;
where &colvar ne .;
var ageo;
by apuper apuperc avisitn avisit cat;
output out=co_2gs mean=gmean std=gstd lclm=glclm uclm=guclm;

```

```

run;

data co_2gs_x (drop=gmean glclm guclm rename=(gmean_x=gmean glclm_x=glclm guclm_x=guclm ));
set co_2gs;
if gmean ne . then gmean_x=exp(gmean);
if glclm ne . then glclm_x=exp(glclm);
if guclm ne . then guclm_x=exp(guclm);
run;

data co_2gs_c;
set co_2gs_x;

if glclm ne . then glclm = 0.01*floor(100*glclm);
if guclm ne . then guclm = 0.01*ceil(100*guclm);

if gstd ^=. then CV=sqrt(exp(gstd*gstd)-1)*100;
if gmean ^=. and CV ^=. then gmean_cv =strip(put(gmean,12.2))||" ("||strip(put(cv,12.3))||")";
if glclm^=. and guclm^=. then glcm_guclm= strip(put(glclm,12.2))||", "||strip(put(guclm,12.2));
if glclm=. and guclm=. then glcm_guclm= 'NA' ||", "||'NA';
run;

proc transpose data=co_2gs_c out=co_2gs_ct( rename=(_name=_stat_ col1=&colvar.));
  by apuper apuperc avisitn avisit cat;
  var gmean_cv glcm_guclm;
run;

data co_3;
  set co_2s_ct co_2gs_ct;
run;

proc sort data=co_3 out=co_4; by apuper apuperc avisitn avisit _stat_; run;

proc transpose data=co_4 out=transpose_&colvar. prefix=&colvar.;
  by apuper apuperc avisitn avisit _stat_;
  id cat;
  var &colvar.;
run;

%mend stats;

%stats(colvar=aval);
%stats(colvar=pchg);

data &paramcd;
merge transpose_aval (in=a drop=_name_)
      transpose_pchg(in=b drop=_name_);
by apuper apuperc avisitn avisit _stat_;
if a or b;
run;

data &paramcd._final;
length label $100.;
set &paramcd.;
if upcase(_stat_) = "N" then do; order = 1; label="n";end;
if upcase(_stat_)='MSG_PCT' then do; order=1.5; label='Missing, n (%)'; end;
if upcase(_stat_)='BLQ_PCT' then do; order=1.75; label='BLOQ, n (%)'; end;
if upcase(_stat_) = "GMEAN_CV" then do; order = 2; label="Geometric Mean (CV%)";end;
if upcase(_stat_) = "GLCM_GUCLM" then do; order = 3; label="95% CI of Geometric Mean";end;
if upcase(_stat_) = "MEDIAN" then do; order = 4; label="Median";end;
if upcase(_stat_) = "Q25_Q75" then do; order = 5; label="Q25, Q75";end;
if upcase(_stat_) = "MIN_MAX" then do; order = 6; label="Min, Max";end;
if upcase(_stat_) = "MEAN_SD" then do; order = 7; label="Mean (SD)";end;
if upcase(_stat_) = "CL95_CU95" then do; order = 8; label="95% CI of Mean";end;

ord = &x.;
run;

proc sort data=&paramcd._final;
by apuper apuperc avisitn avisit order;
run;

%mend param;

%param(paramcd=UMHBM24U, x=2);
%param(paramcd=UMHBMCRE, x=1);

```

```

proc sort data = adbx out=param (keep=paramcd param paramn avalu) nodupkey;
by paramcd;
run;

data final;
length paramcd $8.;
set UMHBMCRE_final(in=a)
    UMHBM24U_final(in=b);
    if a then paramcd = "UMHBMCRE";
    else if b then paramcd = "UMHBM24U";
run;

proc sort data=final;
by paramcd apuper apuperc avisitn avisit order;
run;

data final1;
merge final(in=a) param(in=b);
by paramcd;
if a;
run;

****set pchg to missing for paramcd = 48;
data final2;
set final1;
if paramn = 46 then do;
    array x pchg;;
    do over x;
        x = "";
    end;
end;
if upcase(avisit) = "BASELINE" then do;
    array y pchg;;
    do over y;
        y = "";
    end;
end;
if order in (2 3) then do;
    pchg1 = "";
    pchg2 = "";
    pchg3 = "";
end;
run;

data final3;
set final2;
/*if avisitn = 101 then delete;*/
rename label = txt
    aval1 = trt_4
    aval2 = trt_5
    aval3 = trt_3
    pchg1 = chg_4
    pchg2 = chg_5
    pchg3 = chg_3
    order = txtn;
run;

proc sort data= final3;
by paramn param apuper apuperc avisitn avisit txtn ;
run;

data final3a;
set final3;

if upcase(_stat_) = 'MSG_PCT' and cmiss(trt_3, trt_4, trt_5, chg_3, chg_4, chg_5)=6 then delete;
if upcase(_stat_) = 'BLQ_PCT' and cmiss(trt_3, trt_4, trt_5, chg_3, chg_4, chg_5)=6 then delete;
if upcase(_stat_) = 'BLQ_PCT' then call missing(chg_3, chg_4, chg_5);

if upcase(_stat_) = 'BLQ_PCT' then do;

array ms {3} trt_3 trt_4 trt_5;
do i = 1 to 3;
    if ms{i} = '' then ms{i} = '0';
end;

end;

```

```

if upcase(_stat_) = 'MSG_PCT' then do;

array mb {3} trt_3 trt_4 trt_5;
do i = 1 to 3;
  if mb{i} = '' then mb{i} = '0';
end;

end;

run;

data tflds.t_15_02_04_02_01;
set final3a (drop=paramcd);
run;

data final_dp;
length period $200.;
set final3a;
by paramn param apuper apuperc avisitn avisitn txtn ;
if apuper = 1 then do;
  period = "Period 1";
  THS = &N1THS;
  mcc = &N1mcc;
  sa = &N1saa;
end;
else if apuper = 2 then do;
  period = "Period 2";
  ths = &n2ths;
  mcc = &n2mcc;
  sa = &n2saa;
end;
else if apuper = 3 then do;
  period = "Period 3";
  ths = &n3ths;
  mcc = &n3mcc;
  sa = &n3saa;
end;
else if apuper = 4 then do;
  period = "Period 4";
  ths = &n4ths;
  mcc = &n4mcc;
  sa = &n4saa;
end;
run;

proc sql;
create table page as
select distinct apuper, apuperc, paramn, avisitn
from final_dp
order by paramn, apuper, avisitn;
quit;

data page1;
set page;
by paramn apuper avisitn;
if _n_ = 0 then page = 0;
page+ 1;
run;

proc sql;
create table final_page as
select distinct a.*, b.page
from final_dp as a
left join page1 as b
on a.paramn = b.paramn and a.avisitn = b.avisitn and a.apuper = b.apuper
order by paramn, apuper,avisitn, txtn;
quit;

data final_page;
set final_page end=last;
by paramn apuper avisitn txtn;
if last then call symputx("page", page);
run;

%let tfl = %str(T_15_02_04_02_01);

```

```

%let title1 = %str(Table 15.2.4.2.1 Descriptive Statistics of MHBMA in 24-hour Urine Collection - PP Set);
%let tflno=&tfl.;

/* Standard - leave this */
options number nodate orientation=landscape missing=' ';
ods escapechar='$';
%let linetop = \brdrt\brdrs\brdrw30; * needs to be 1.5pt so calculated in twips (1/20 pt) ;
%let linebot = \brdrb\brdrs\brdrw30;
/* Standard - macro for paging */
%macro outrtf(blankn=130, halfblnk=N);

%if &halfblnk=N %then %let halfblnk=;
%else %if &halfblnk=Y %then %let halfblnk=\-;

ods path stdlib.t106343 (read) ;
ods results off;
ods rtf toc_data file="cvn/projects/prj/data/000000106343/TFL/&TFL_Part./Tables/&tflno..rtf" style=t106343 startpage=yes headery=14
40 footery=1440 ;
ods noproctitle;
%do i=1 %to &page;

title ;
footnote;
%let wd=0;
ods proclabel = ' ' ;

data comp;
    set final_page end=eof;
    where page=&i;

    /* Amend title as needed */
    _firtitl="%title1.";
    _upcas=(length("Path: &TFLpath.")-length(compress("Path:&TFLpath.", 'ABCDEFGHIJKLMNOPQRSTUVWXYZ')))/2;
    len=&blankn.-length("(page &i of &page)");
    call symput('pran', compress(put(paramn,best.)));

if eof then do;
    call symput('_FSRTITL', trim(left(_firtitl)));
    call symput('_blankn', compress(put(len,best.)));
    call symput('period', strip(apuperc));
    call symput('param', strip(param));
    call symput('N3', strip(put(sa, best.)));
    call symput('N4', strip(put(th, best.)));
    call symput('N5', strip(put(mcc, best.)));
end;
drop _firtitl _upcas len;
run;

ods listing close;

proc report data = comp headline headskip nowd spacing=1 split = '$' %if &i=1 %then %do; contents=' ' %end; %else %do; contents='' %
end;;;
column page paramn apuper avisitn avisit txtn txt ("THSm2.2$(N=&N4)&linebot" trt_4 chg_4 ) ("mCC$(N=&N5)&linebot" trt_5 chg_5)
("SA$(N=&N3)&linebot" trt_3 chg_3);
define paramn / order order = internal noprint;
define page / order order = internal noprint;
define avisitn / order order = internal noprint;
define apuper / order order = internal noprint;

define txtn / order order = internal noprint;
define avisit / "Timepoint" order order=internal style={just=left cellwidth=0.9cm} style(header)={just=left} ;
define txt / "Statistic" display style={just=left cellwidth=1.9cm} style(header)={just=left} ;
define trt_3 / "Value" display style={JUST=c cellwidth=1.3cm} style(header)={just=center} ;
define trt_4 / "Value" display style={just=c cellwidth=1.3cm} style(header)={just=center} ;
define trt_5 / "Value" display style={just=c cellwidth=1.3cm} style(header)={just=center};
%if &pran = 45 %then %do;
define chg_3 / "% Change(*)" display style={JUST=c cellwidth=1cm} style(header)={just=center};
define chg_4 / "% Change(*)" display style={just=c cellwidth=1cm} style(header)={just=center};
define chg_5 / "% Change(*)" display style={just=c cellwidth=1cm} style(header)={just=center};
%end;
%if &pran = 46 %then %do;
define chg_3 /noprint;
define chg_4 /noprint;
define chg_5 /noprint ;

```

```

%end;

compute after avisitn;
  line " ";
endcomp;

compute before _page_ / style={just=left protectspecialchars=off};
  line "\b\fs24\sa24&_FSRTITL." ; * \b = bold, \fs24 is font size 12pt, \sa24 is space after 12pt;
  line " ";
  line "Parameter (units): &param";
  LINE "Product Use Time Period: &period";
  line "&linebot";
endcomp;

compute after _page_ / style={just=left protectspecialchars=off pretext="&linetop."};
  line 'Note: mCC = Menthol Conventional cigarettes; SA = Smoking abstinence; THSm2.2 = Tobacco Heating System 2.2 Menthol.';
  LINE 'Note: * % Change from baseline, where baseline is defined as the last assessment prior to first randomized product use in mC
C / THS 2.2 Menthol arms or the last assessment prior to 10AM on Day 1 in the SA arm.';
  line "Note: 'Missing' percentages are based on the number of subjects indicated in the column header (N), while 'BLOQ' percentage
s are based on the number of subjects being summarized (n).";
  line '';
  line 'Appendix 15.3.3.1';
  line "Study ID:ZRRM-REXA-08-US          Program: &TFLprg          Status: &status" &_blankn.*"\-\" "&sysdate" &_blankn.*"\-\" "(Pa
ge &i of &page)";
  endcomp;
run;
%end;
ods rtf close;
ods results on;
ods path sashelp.tmplmst (read);

%mend ;

%outrtf(blankn=30, halfblnk=N);
ods listing;

%m_logchk;

```